

TUPOLI Suspended 55 LED 24W 4000K Frost 1181mm

DESCRIPTION

- Luminaire with direct luminous flux distribution, opal polycarbonate diffuser and aluminium body e no finishing.



IP40





MAIN FEATURES

Volume (dm3)	1.3
Weight (Kg)	1.3
Glow-wire Resistance	850°C
Input	220-240V~/50-60Hz
Control	ON/OFF Power Supply


TECHNICAL FEATURES


MAX Power (W)	24
Maximum Value (cd/Klm)	260
% ULOR	12
% DLOR	88
% LOR	100
Luminous Flux Maintenance	L70
MacAdam Ellipse	3
LED Degradation/Mortality	F10
Total Flux (lm)	3241
System Power (W)	26
Flux/Power (lm/W)	135
Color Temperature	4000K
Color Rendering Index (CRI)	>80
LED Efficiency	167 lm/W @Tc=65°C



STANDARDS

DIRECTIVE 2011/65/EU of 8 June 2011 + COMMISSION DELEGATED DIRECTIVE (EU) 2015/863 of 31 March 2015 RoHS2
DIRECTIVE 2014/30/EU of 26 February 2014
EN 50581:2012 | EN 55015:2006+A1:2007+A2:2009 | EN 60335-1:2012 | EN 60598-1: 2014 | EN 60598-2-1: 1990 | EN 60598-2-13: 2006 | EN 60598-2-2: 2014 | EN 60598-2-22: 2014 | EN 60598-2-25: 2009 | EN 60598-2-4: 2017 | EN 61000-4-2:2009;EN 61000-4-3:2006 + A1:2008;EN 61000-4-4:2004;EN 61000-4-5:2006;EN 61000-4-6:2009 | EN 61547:2009
LOW VOLTAGE DIRECTIVE 2014/35/EU of 26 February 2014





COMPONENTS



B	2xSuspension system/Sistema suspensão White 1000mm Tupoli 55	35.49.001.08.32
	2xSuspension system/Sistema suspensão White 3000mm Tupoli 55	35.49.001.08.33
	2xSuspension system/Sistema suspensão White 5000mm Tupoli 55	35.49.002.08.75



C2	Recessed ceiling cup WhiteTupoli ON/OFF+KIT (1m) Ø80x2mm	35.49.001.08.49
	Recessed ceiling cup WhiteTupoli ON/OFF+KIT (3m) Ø80x2mm	35.49.002.08.64
	Recessed ceiling cup White Tupoli ON/OFF (3m) Ø80x2mm	35.49.002.08.63
	Recessed ceiling cup White Tupoli ON/OFF (5m) Ø80x2mm	35.49.002.08.71
	Recessed ceiling cup WhiteTupoli ON/OFF+KIT (5m) Ø80x2mm	35.49.002.08.72
	Recessed ceiling cup White Tupoli ON/OFF (1m) Ø80x2mm	35.49.001.08.31



C1	Surface ceiling cup White Tupoli ON/OFF+KIT (3m) Ø62x36mm	35.49.002.08.60
	Surface ceiling cupTupoli ON/OFF (5m) Ø62x36mm	35.49.002.08.67
	Surface ceiling cup White Tupoli ON/OFF+KIT (5m) Ø62x36mm	35.49.002.08.68
	Surface ceiling cup White Tupoli ON/OFF+KIT (1m) Ø62x36mm	35.49.001.08.46
	Surface ceiling cup White Tupoli ON/OFF (1m) Ø62x36mm	35.49.001.08.30
	Surface ceiling cup White Tupoli ON/OFF (3m) Ø62x36mm	35.49.002.08.59

OPTIONS

EMERGENCY

Emergency KIT 3W LED constant current 1H 30-220V

35.00.003.01.23

