Climar





Astra



ASTRA Suspended 90 LD/LI LED

Astra



Enhancing your visual environment – full family of highly stylized luminaires offering excellent performance while creating a uniquely dramatic effect.





ASTRA Trimless 90 LD LED, Hotel Tryp Oriente, Portugal

Suspended, surface, recessed and wall mounted solutions




ASTRA Suspended 90 LD LED







ASTRA Suspended 150 LD LED, Hotel 3K Europa, Portugal

Maximum efficiency – High quality Zhaga-compatible LED engines



ASTRA Surface 150 LD LED, Porto Editora, Portugal





ASTRA Trimless 90 LD LED, Hotel Tryp Oriente, Portugal

Personalize your space

Broad range of configuration options – colour, diameter, power, suspension type and tilting angle – ASTRA family provides inspiration for extraordinary ideas.

Direct and indirect lighting

Simultaneous direct and indirect lighting for suspended solutions. The indirect lighting component provides a soft, warm feel to the room.

ASTRA Suspended 90 LD/LI LED




Compact design with unique details

Monoblock construction, seamlessly welded outer aluminium profile, no screws, magnetic clamping system, ... exceptional surfaces and finishes!

ASTRA Suspended 90 LD LED, ASTRA Surface 90 LD LED





ASTRA Suspended 150 LD/LI LED, Atlanta LDA, Portugal

Easy installation

Designed and engineered to allow installation without the need to open the luminaire, minimising installation cost.





Custom lighting

Custom solutions are available to meet your unique application. ASTRA family is available in diameters up to 6 m and in any RAL colour required.


imar Lighting . ASTR/

Astra Suspended 90


Model




Mounting



Suspended S2



Suspended S3



Light Distribution





Diameter / Power

Optics

Features

Ø400 mm

LD : 16W / 23W LD/LI: 28W / 39W



Ø550 mm

LD : 27W / 42W LD/LI: 43W / 63W




Ø830 mm

LD: 53W / 85W LD/LI: 77W / 116W





Ø1110 mm

LD: 96W / 155W LD/LI: 128W / 196W









LED

3000 K 4000 K

Tunable White *

Control

On/Off DALI

Finishing

White

Black

Multicolor *

General

Emergency 1h - 3h*
IP20 - IP44*
Class I

Astra Surface 90

Model Mounting Light Distribution | 90mm | 190mm | Light Distribution |

Diameter / Power

Optics

Features

Ø400 mm

LD: 16W / 23W



Ø550 mm

LD: 27W / 42W




Ø830 mm


LD: 53W / 85W




Ø1110 mm

LD: 96W / 155W







LED

3000 K

4000 K

Tunable White *

Control

On/Off

DALI

Finishing

White

Black

Multicolor *

General

Emergency 1h - 3h*
IP20 - IP44*
Class I

Astra Trimless 90

Model Mounting Light Distribution Light Distribution

Diameter / Power

Optics

Features

Ø400 mm

LD: 16W / 23W



Ø550 mm

LD: 27W / 42W




Ø830 mm


LD: 53W / 85W




Ø1110 mm

LD: 96W / 155W







LED

3000 K

4000 K

Tunable White *

Control

On/Off

DALI

Finishing

White

Black

Multicolor *

General


Emergency 1h - 3h*
IP20 - IP44*
Class I

Astra Suspended 150


Model




Mounting



Suspended S2



Suspended S3



Light Distribution





Diameter / Power

Optics

Features

Ø400 mm

LD : 18W / 29W LD/LI: 30W / 45W



Ø650 mm

LD : 36W / 53W LD/LI: 52W / 74W




Ø800 mm

LD : 60W / 89W LD/LI: 84W / 120W




Ø1000 mm


LD : 96W / 142W LD/LI: 128W / 183W




Ø1200 mm

LD : 144W / 212W LD/LI: 184W / 264W







LED

3000 K

4000 K

Tunable White *

Control

On/Off

DALI

Finishing

White

Black

Multicolor *

General

Emergency 1h - 3h*

IP20 - IP44*

Class I

Astra Surface 150

Model Mounting Light Distribution Light Distribution

Climar Lighting . ASTRA

Diameter / Power

Optics

Features

LED

3000 K

4000 K
Tunable White *

Ø400 mm

LD: 18W / 29W




Ø650 mm

LD: 36W / 53W



Ø800 mm

LD: 60W / 89W




Ø1000 mm


LD: 96W / 142W



Ø1200 mm

LD: 144W / 212W





Control

On/Off

DALI

Finishing

White

Black

Multicolor *

General

Emergency 1h - 3h*
IP20 - IP44*

Class I

Astra Trimless 150

Model Mounting Light Distribution 150mm

Climar Lighting . ASTRA

Diameter / Power

Optics

Features

LED

3000 K

4000 K
Tunable White *

Ø400 mm

LD: 18W / 29W



Ø650 mm

LD: 36W / 53W




Ø800 mm

LD: 60W / 89W




Ø1000 mm


LD: 96W / 142W



Ø1200 mm

LD: 144W / 212W





Control

On/Off

DALI

Finishing

White

Black

Multicolor *


General

Emergency 1h - 3h*

IP20 - IP44*

Class I

Highlights



LED technology evolution results in continuous changes in the luminous efficiency of the LED. The information provided by the catalogue should therefore be referred to the date of publication – for regularly updated data, technical and photometric information, quality certificates and product data sheets please refer to our website **www.climarlighting.com.**

This brochure nullifies all previous versions and it may be changed without notice.

Five-year guarantee

The products presented on this brochure are covered by a 5-year manufacturer's guarantee in accordance with the terms of guarantee at www.climarlighting.com.



Climar

Concept
BYBEAU

Design / Photo
Climar Lighting
Print
Orgal Impressores
DVM.215.17.0 . 11.2017
© Copyright Climar
All rights reserved.



Climar - Indústria de Iluminação, S.A. **Headquarters:** Estrada Real, 50 . 3750-866 Borralha . Portugal **t** +351 234 690 330 | **m** +351 915 599 110 | geral@climar.pt | www.facebook.com/climar.lighting **London Office:** 31 – 35 Kirby Street, London EC1N 8TE . UK **t** 020 7492 1707 | **m** 07496 378770 | jason.perks@climarlighting.co.uk





