

OPPOSITE 2 DYNAWHITE

indoor lighting

Luminaire for recessed installation in ceilings or ceiling grids
 BODY: painted aluminum sheet, white painted steel frame; a version for 625x625mm ceilings also possible
 DIFFUSER: microprismatic PMMA,
 UGRPOWER SUPPLY: remote electronic power supply
 3xS TECHNOLOGY: save money, save energy, save time
 OTHER: dynamic color temperature changing system within a range between 2700K-6500K



Concave microprismatic PMMA diffuser, DALI version, white, 81° light distribution, UGR <19

3983061	OPPOSITE 2 IN DYNAWHITE 597	LED 2700K + LED 6500K	4000 lm	230V AC	50W	5.50
3983161	OPPOSITE 2 IN DYNAWHITE 622	LED 2700K + LED 6500K	4000 lm	230V AC	50W	5.50

Convex microprismatic PMMA diffuser, DALI version, white, 81° light distribution, UGR <19

3982061	OPPOSITE 2 OUT DYNAWHITE 597	LED 2700K + LED 6500K	4000 lm	230V AC	50W	5.00
3982161	OPPOSITE 2 OUT DYNAWHITE 622	LED 2700K + LED 6500K	4000 lm	230V AC	50W	5.00