

## TUPOLI Suspended 55 LED 48W 3000K Frost 2305mm

### DESCRIPTION

- Luminaire with direct luminous flux distribution, opal polycarbonate diffuser and aluminium body e no finishing.





### MAIN FEATURES

Volume (dm3)	2.4
Weight (Kg)	2.4
Glow-wire Resistance	850°C
Input	220-240V~/50-60Hz
Control	ON/OFF Power Supply


### TECHNICAL FEATURES


MAX Power (W)	48
Maximum Value (cd/Klm)	260
% ULOR	12
% DLOR	88
% LOR	100
Luminous Flux Maintenance	L70
LED Degradation/Mortality	F10
Total Flux (lm)	6193
System Power (W)	52
Color Temperature	3000K
LED Efficiency	160 lm/W @ Tc=65°C
Color Rendering Index (CRI)	>80
MacAdam Ellipse	3



### STANDARDS

DIRECTIVE 2011/65/EU of 8 June 2011 + COMMISSION DELEGATED DIRECTIVE (EU) 2015/863 of 31 March 2015 RoHS2  
DIRECTIVE 2014/30/EU of 26 February 2014  
EN 50581:2012 | EN 55015:2006+A1:2007+A2:2009 | EN 60335-1:2012 | EN 60598-1: 2014 | EN 60598-2-1: 1990 | EN 60598-2-13: 2006 | EN 60598-2-2: 2014 | EN 60598-2-22: 2014 | EN 60598-2-25: 2009 | EN 60598-2-4: 2017 | EN 61000-4-2:2009;EN 61000-4-3:2006 + A1:2008;EN 61000-4-4:2004;EN 61000-4-5:2006;EN 61000-4-6:2009 | EN 61547:2009  
LOW VOLTAGE DIRECTIVE 2014/35/EU of 26 February 2014





## COMPONENTS



### SUSPENSION SYSTEM

<b>B</b>	2xSuspension system/Sistema suspensão White 1000mm Tupoli 55	<b>35.49.001.08.32</b>
	2xSuspension system/Sistema suspensão White 3000mm Tupoli 55	<b>35.49.001.08.33</b>
	2xSuspension system/Sistema suspensão White 5000mm Tupoli 55	<b>35.49.002.08.75</b>



### RECESSED CEILING CUP

<b>C2</b>	Recessed ceiling cup WhiteTupoli ON/OFF+KIT (1m) Ø80x2mm	<b>35.49.001.08.49</b>
	Recessed ceiling cup WhiteTupoli ON/OFF+KIT (3m) Ø80x2mm	<b>35.49.002.08.64</b>
	Recessed ceiling cup White Tupoli ON/OFF (3m) Ø80x2mm	<b>35.49.002.08.63</b>
	Recessed ceiling cup White Tupoli ON/OFF (5m) Ø80x2mm	<b>35.49.002.08.71</b>
	Recessed ceiling cup WhiteTupoli ON/OFF+KIT (5m) Ø80x2mm	<b>35.49.002.08.72</b>
	Recessed ceiling cup White Tupoli ON/OFF (1m) Ø80x2mm	<b>35.49.001.08.31</b>



### SURFACE CEILING CUP

<b>C1</b>	Surface ceiling cup White Tupoli ON/OFF+KIT (3m) Ø62x36mm	<b>35.49.002.08.60</b>
	Surface ceiling cupTupoli ON/OFF (5m) Ø62x36mm	<b>35.49.002.08.67</b>
	Surface ceiling cup White Tupoli ON/OFF+KIT (5m) Ø62x36mm	<b>35.49.002.08.68</b>
	Surface ceiling cup White Tupoli ON/OFF+KIT (1m) Ø62x36mm	<b>35.49.001.08.46</b>
	Surface ceiling cup White Tupoli ON/OFF (1m) Ø62x36mm	<b>35.49.001.08.30</b>
	Surface ceiling cup White Tupoli ON/OFF (3m) Ø62x36mm	<b>35.49.002.08.59</b>

**OPTIONS**

**EMERGENCY**

Emergency KIT 3W LED constant current 1H 30-220V

**35.00.003.01.23**

