


TILIA 3

Dimensions:	550x550 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polycarbonate (PC)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
52121	IN-42NU4/PC34	IP44		4x30	4xE27		0,0	24
52122	E-46LNU4/PC34	IP44		4x24	4xG24q3		0,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56371	LED-4L36C03NU4/PC34 3000	IP44	3000	36	5150	3450		0,0	60
56373	LED-4L36C07NU4/PC34 3000	IP44	3000	75	9670	6480		0,0	60
56871	LED-4L36C03NU4/PC34 4000	IP44	4000	36	5430	3640		0,0	60
56873	LED-4L36C07NU4/PC34 4000	IP44	4000	75	10200	6830		0,0	60
Dimmable									
56372	LED-4L36C03NU4/PC34 DALI 3000	IP44	3000	36	5150	3450		0,0	60
56374	LED-4L36C07NU4/PC34 DALI 3000	IP44	3000	75	9670	6480		0,0	60
56872	LED-4L36C03NU4/PC34 DALI 4000	IP44	4000	36	5430	3640		0,0	60
56874	LED-4L36C07NU4/PC34 DALI 4000	IP44	4000	75	10200	6830		0,0	60