



DELIA 2 - PMMA

Dimensions:	ø 400 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polymethylmetacrylate (PMMA)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56120	IN-22KN83/PM23	IP44		2x30	2xE27		1,4	24
56122	E-26KN83/PM23	IP44		2x26	2xG24q3		1,7	24
Sensor								
56126	IN-22KN83/PM23 HF	IP44		2x30	2xE27		1,5	24
Emergency combined								
56129	NKC-226/13/PM23	IP44		2x26	2xG24q3	1	2,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56308	LED-1L16C07KN83/PM23 3000	IP54	3000	28	3690	2580		1,8	60
53348	LED-1L16B07KN83/PM23 3000	IP54	3000	36	4850	3400		1,8	60
56806	LED-1L16C07KN83/PM23 4000	IP54	4000	28	3890	2720		1,8	60
53848	LED-1L16B07KN83/PM23 4000	IP54	4000	36	5070	3550		1,8	60
Sensor									
56309	LED-1L16C07KN83/PM23 HF 3000	IP54	3000	28	3690	2580		1,8	60
53354	LED-1L16B07KN83/PM23 HF 3000	IP54	3000	36	4850	3400		1,8	60
56809	LED-1L16C07KN83/PM23 HF 4000	IP54	4000	28	3890	2720		1,8	60
53854	LED-1L16B07KN83/PM23 HF 4000	IP54	4000	36	5070	3550		1,8	60
Dimmable									
56310	LED-1L16C07KN83/PM23 DALI 3000	IP54	3000	28	3690	2580		1,8	60
53352	LED-1L16B07KN83/PM23 DALI 3000	IP54	3000	36	4850	3400		1,8	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
56810	LED-1L16C07KN83/PM23 DALI 4000	IP54	4000	28	3890	2720		1,8	60
53852	LED-1L16B07KN83/PM23 DALI 4000	IP54	4000	36	5070	3550		1,8	60
Emergency combined									
56313	LED-1L16C07KN83/PM23/NK1W 3000	IP54	3000	28	3690	2580	3	1,8	60
53356	LED-1L16B07KN83/PM23/NK1W 3000	IP54	3000	36	4850	3400	3	1,8	60
56813	LED-1L16C07KN83/PM23/NK1W 4000	IP54	4000	28	3890	2720	3	1,8	60
53856	LED-1L16B07KN83/PM23/NK1W 4000	IP54	4000	36	5070	3550	3	1,8	60
Emergency combined + sensor									
56314	LED-1L16C07KN83/PM23/NK1W HF 3000	IP54	3000	28	3690	2580	3	1,8	60
56315	LED-1L16B07KN83/PM23/NK1W HF 3000	IP54	3000	36	4850	3400	3	1,8	60
56814	LED-1L16C07KN83/PM23/NK1W HF 4000	IP54	4000	28	3890	2720	3	1,8	60
56815	LED-1L16B07KN83/PM23/NK1W HF 4000	IP54	4000	36	5070	3550	3	1,8	60
Two-circuits									
53349	LED-1L16B07KN83/PM23 2/1 3000	IP54	3000	36	4850	3400		1,8	60
53849	LED-1L16B07KN83/PM23 2/1 4000	IP54	4000	36	5070	3550		1,8	60
Corridor									
56311	LED-1L16C07KN83/PM23 DALI HF CORR 3000	IP54	3000	28	3690	2580		1,8	60
56312	LED-1L16B07KN83/PM23 DALI HF CORR 3000	IP54	3000	36	4850	3400		1,8	60
56811	LED-1L16C07KN83/PM23 DALI HF CORR 4000	IP54	4000	28	3890	2720		1,8	60
56812	LED-1L16B07KN83/PM23 DALI HF CORR 4000	IP54	4000	36	5070	3550		1,8	60