## Datasheet

# FOCUS M

Manufacture: NEKO LIGHTING AG Type: FOCUS M Tracklight FOM1-8301242F-BB



#### General

#### Indoor

- Tracklight
- Tracklight
- Version: round
- Housing: black
- Reflector: black
- System Output: 3100lm
- IP 20

LED

### 

- 3000K
- CRI80
- 4000lm
- 50000h@L80B10
- SDCM: 3

#### Optics

- Beam angle: 18°
- UGR <19


#### Electric

- LED Driver: ON-OFF
- LED Power: 38W
- System Power: 42W
- 36V
- 1050mA
- Dimensions
- Measurement: Ø90mm
- Height: 200mm
- Net Weight: 1700g
- Gross Weight: 1900g
- Pivot: max. 90°
- Rotation: 355°


#### Description


Tracklight round made from die-cast aluminium with black powder-coating finish (RAL 9005) and black reflector; ON-OFF Driver; LED 38W; measurement Ø90mm; tracklights length 200mm; measurements adapter 192mm x 76mm x 37mm; luminaire's weight is approximately 1700g; rotation 355° and pivot max. 90°; CCT 3000K with an LED Output of 4000lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; narrow beam characteristic with 18° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)

#### Light distribution



#### **Technical drawing**





The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.



www.nekolighting.com