


# DELIA 5

<b>Dimensions:</b>	ø 900 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	opal polymethylmetacrylate (PMMA)
<b>Shade attach.:</b>	two-step clamp holders
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
53515	IN-62KN11/PM26	IP44		6x30	6xE27		9,0	24
53516	E-66KN11/PM26	IP44		6x24	G5		9,5	24
53517	E-67KN11/PM26	IP44		6x36	6x2G10		9,5	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
56346	LED-9L52B07KN11/PM26 3000	IP54	3000	104	15310	10720		9,9	60
48232	LED-9L52B10KN11/PM26 3000	IP54	3000	165	22180	15530		10,0	60
56846	LED-9L52B07KN11/PM26 4000	IP54	4000	104	16000	11200		9,9	60
48732	LED-9L52B10KN11/PM26 4000	IP54	4000	165	23170	16220		10,0	60
<b>Dimmable</b>									
56347	LED-9L52B07KN11/PM26 DALI 3000	IP54	3000	104	15310	10720		9,9	60
48235	LED-9L52B10KN11/PM26 DALI 3000	IP54	3000	165	22180	15530		10,1	60
56847	LED-9L52B07KN11/PM26 DALI 4000	IP54	4000	104	16000	11200		9,9	60
48735	LED-9L52B10KN11/PM26 DALI 4000	IP54	4000	165	23170	16220		10,1	60
<b>Two-circuits</b>									
56348	LED-9L52B07KN11/PM26 2/1 3000	IP54	3000	104	15310	10720		9,9	60
48233	LED-9L52B10KN11/PM26 2/1 3000	IP54	3000	165	22180	15530		10,0	60
56848	LED-9L52B07KN11/PM26 2/1 4000	IP54	4000	104	16000	11200		9,9	60
48733	LED-9L52B10KN11/PM26 2/1 4000	IP54	4000	165	23170	16220		10,0	60