



# DELIA 3 - PC

<b>Dimensions:</b>	ø 500 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	opal polycarbonate (PC)
<b>Shade attach.:</b>	two-step clamp holders
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
56130	IN-32KN94/PC24	IP44		3x40	3xE27		2,5	24
56131	E-26KN94/PC24 32W	IP44		2x32	2xGX24q3		2,9	24
56132	E-27KN94/PC24	IP44		2x36	2xG10		2,9	24
<b>Sensor</b>								
56137	IN-32KN94/PC24 HF	IP44		3x40	3xE27		2,6	24
<b>Emergency combined</b>								
56142	NKC-232/16/PC24	IP44		2x32	2xGX24q3	1	3,2	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
56320	LED-3L53C07KN94/PC24 3000	IP54	3000	35	4750	3140		2,6	60
56324	LED-3L53C10KN94/PC24 3000	IP54	3000	53	6780	4470		2,6	60
56820	LED-3L53C07KN94/PC24 4000	IP54	4000	35	5010	3310		2,6	60
56824	LED-3L53C10KN94/PC24 4000	IP54	4000	53	7150	4720		2,6	60
<b>Dimmable</b>									
56322	LED-3L53C07KN94/PC24 DALI 3000	IP54	3000	35	4750	3140		2,6	60
56326	LED-3L53C10KN94/PC24 DALI 3000	IP54	3000	53	6780	4470		2,6	60
56822	LED-3L53C07KN94/PC24 DALI 4000	IP54	4000	35	5010	3310		2,6	60
56826	LED-3L53C10KN94/PC24 DALI 4000	IP54	4000	53	7150	4720		2,6	60
<b>Emergency combined</b>									
56328	LED-3L53C07KN94/PC24/NK1W 3000	IP54	3000	35	4750	3140	3	2,6	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
56329	LED-3L53C10KN94/PC24/NK1W 3000	IP54	3000	53	6780	4470	3	2,6	60
56828	LED-3L53C07KN94/PC24/NK1W 4000	IP54	4000	35	5010	3310	3	2,6	60
56829	LED-3L53C10KN94/PC24/NK1W 4000	IP54	4000	53	7150	4720	3	2,6	60