


# ADRIA L3

<b>Dimensions:</b>	ø 400 mm
<b>Color:</b>	white
<b>Type:</b>	ceiling mounted
<b>Shade:</b>	handmade three-layer glass TRIPLEX OPAL (matt finish)
<b>Shade attach.:</b>	steel holder (ø150mm)
<b>Pendant:</b>	wire
<b>Length of pendant:</b>	L100 - 1000mm, L200 - 2000mm
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
42464	ZL11/096/L100 B	IP40		150	E27		3,8	24
42465	ZL11/096/L200 B	IP40		150	E27		3,9	24
42466	E-26ZL11/096/L100 B	IP40		2x26	2xG24q3		4,1	24
42467	E-26ZL11/096/L200 B	IP40		2x26	2xG24q3		4,2	24
45332	E-28ZL11/096/L100 B	IP40		2x42	2xGX24q4		4,1	24
45333	E-28ZL11/096/L200 B	IP40		2x42	2xGX24q4		4,2	24
<b>Dimmable</b>								
45338	ES-26ZL11/096/L100 B DALI	IP40		2x26	2xG24q3		4,1	24
45339	ES-26ZL11/096/L200 B DALI	IP40		2x26	2xG24q3		4,2	24
<b>Emergency combined</b>								
45340	NKC-226ZL/13/096/L100 B	IP40		2x26	2xG24q3	1	4,2	24
45341	NKC-226ZL/13/096/L200 B	IP40		2x26	2xG24q3	1	4,3	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
60264	LED-5L06C06ZL11/096/L100 B 3000	IP40	3000	29	3900	3430		5,2	60
60265	LED-5L06C06ZL11/096/L200 B 3000	IP40	3000	29	3900	3430		5,2	60
60764	LED-5L06C06ZL11/096/L100 B 4000	IP40	4000	29	4110	3620		5,2	60
60765	LED-5L06C06ZL11/096/L200 B 4000	IP40	4000	29	4110	3620		5,2	60
<b>Dimmable</b>									
60266	LED-5L06C06ZL11/096/L100 B DALI 3000	IP40	3000	29	3900	3430		5,2	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
60267	LED-5L06C06ZL11/096/L200 B DALI 3000	IP40	3000	29	3900	3430		5,2	60
60766	LED-5L06C06ZL11/096/L100 B DALI 4000	IP40	4000	29	4110	3620		5,2	60
60767	LED-5L06C06ZL11/096/L200 B DALI 4000	IP40	4000	29	4110	3620		5,2	60