

## SENSE 100 Round



Manufacture: NEKO LIGHTING AG

Type: SENSE Modular Downlight SSR1-9302013F-WM

### General

- Indoor
- Downlight
- Adjustable
- Recessed
- Version: round
- Housing: white
- Reflector: matt
- System Output: 850lm
- IP 20



### LED

- 3000K
- CRI90
- 1300lm
- 50000h@L80B10
- SDCM: 3

### Optics

- Beam angle: 20°
- UGR <19

### Electric

- LED Driver: ON-OFF
- LED Power: 13W
- System Power: 15W
- 36V
- 350mA


### Dimensions

- Measurement: Ø110mm
- Cutout: Ø100mm
- Height: 121mm
- Ceiling height: 171mm
- Net Weight: 470g
- Gross Weight: 700g
- Pivot: max. 30°
- Rotation: 355°


### Description

Round recessed ceiling downlight made of die-cast aluminium with white powder-coating finish (RAL 9016) and matt reflector; ON-OFF Driver; LED 13W; measurement Ø110mm; ceiling cutout of Ø100mm with a narrow mounting trim; luminaire's weight is approximately 470g; rotation 355° and pivot max. 30°; CCT 3000K with an LED Output of 1300lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; narrow beam characteristic with 20° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)


### Light distribution



### Technical drawing



Ø100mm



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.