

TUPOLI I-LIGHT 70 Suspended 1459mm 40° 35W 940

DESCRIPTION

- Luminaire with, clear polycarbonate diffuser and aluminium body e
ral 9005 matt black finish.






MAIN FEATURES

Weight (Kg)	3.3
Glow-wire Resistance	850°C
Input	220-240V~/50-60Hz
Control	ON/OFF Power Supply


TECHNICAL FEATURES

Luminous Flux Maintenance	L80
MAX Power (W)	35
Maximum Value (cd/Klm)	1557
% DLOR	100
% LOR	100
Total Flux (lm)	4557
System Power (W)	35
Color Temperature	4000K
Color Rendering Index (CRI)	>90
LED Degradation/Mortality	B10
LED Efficiency	143 lm/W @Tc=65°C
MacAdam Ellipse	3



STANDARDS

DIRECTIVE 2011/65/EU of 8 June 2011 + COMMISSION
DELEGATED DIRECTIVE (EU) 2015/863 of 31 March 2015 RoHS2
DIRECTIVE 2014/30/EU of 26 February 2014
EN 50581:2012 | EN 55015:2006+A1:2007+A2:2009 | EN 60335-
1:2012 | EN 60598-1: 2014 | EN 60598-2-1: 1990 | EN 60598-2-13:
2006 | EN 60598-2-2: 2014 | EN 60598-2-22: 2014 | EN 60598-2-25:
2009 | EN 60598-2-4: 2017 | EN 61000-4-2:2009;EN 61000-4-
3:2006 + A1:2008;EN 61000-4-4:2004;EN 61000-4-5:2006;EN
61000-4-6:2009 | EN 61547:2009
LOW VOLTAGE DIRECTIVE 2014/35/EU of 26 February 2014



COMPONENTS



SUSPENSION SYSTEM

B 2xSuspension system/Sistema suspensão Black 1000mm Tupoli 70	35.49.002.08.97
2xSuspension system/Sistema suspensão Black 3000mm Tupoli 70	35.49.002.08.98
2xSuspension system/Sistema suspensão Black 5000mm Tupoli 70	35.49.002.08.99



SURFACE CEILING CUP

C1 Surface ceiling cup White Tupoli ON/OFF (1m) Ø62x36mm	35.49.001.08.30
Surface ceiling cup White Tupoli ON/OFF (3m) Ø62x36mm	35.49.002.08.59
Surface ceiling cupTupoli ON/OFF (5m) Ø62x36mm	35.49.002.08.67



RECESSED CEILING CUP

C2 Recessed ceiling cup White Tupoli ON/OFF (1m) Ø80x2mm	35.49.001.08.31
Recessed ceiling cup White Tupoli ON/OFF (3m) Ø80x2mm	35.49.002.08.63
Recessed ceiling cup White Tupoli ON/OFF (5m) Ø80x2mm	35.49.002.08.71