


ADRIA P2

Dimensions:	ø 300 mm
Color:	white
Type:	ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	steel holder (ø110mm)
Pendant:	rod
Length of pendant:	a1 - 200mm, a2 - 400mm, a3 - 600mm, a4 - 800mm, a5 - 1000mm
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
42132	Z11/094/a1 B	IP40		100	E27		2,1	24
42133	Z11/094/a2 B	IP40		100	E27		2,2	24
42134	Z11/094/a3 B	IP40		100	E27		2,3	24
42135	Z11/094/a4 B	IP40		100	E27		2,3	24
42136	Z11/094/a5 B	IP40		100	E27		2,4	24
43180	E-25Z11/094/a1 B	IP40		2x18	2xG24q2		2,5	24
43181	E-25Z11/094/a2 B	IP40		2x18	2xG24q2		2,6	24
43182	E-25Z11/094/a3 B	IP40		2x18	2xG24q2		2,7	24
43183	E-25Z11/094/a4 B	IP40		2x18	2xG24q2		2,7	24
43184	E-25Z11/094/a5 B	IP40		2x18	2xG24q2		2,8	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
60035	LED-5L06C04Z11/094/a1 B 3000	IP40	3000	22	2970	2610		3,1	60
60036	LED-5L06C04Z11/094/a2 B 3000	IP40	3000	22	2970	2610		3,1	60
60037	LED-5L06C04Z11/094/a3 B 3000	IP40	3000	22	2970	2610		3,1	60
60038	LED-5L06C04Z11/094/a4 B 3000	IP40	3000	22	2970	2610		3,1	60
60039	LED-5L06C04Z11/094/a5 B 3000	IP40	3000	22	2970	2610		3,1	60
60535	LED-5L06C04Z11/094/a1 B 4000	IP40	4000	22	3130	2760		3,1	60
60536	LED-5L06C04Z11/094/a2 B 4000	IP40	4000	22	3130	2760		3,1	60
60537	LED-5L06C04Z11/094/a3 B 4000	IP40	4000	22	3130	2760		3,1	60
60538	LED-5L06C04Z11/094/a4 B 4000	IP40	4000	22	3130	2760		3,1	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
60539	LED-5L06C04Z11/094/a5 B 4000	IP40	4000	22	3130	2760		3,1	60

Dimmable

60040	LED-5L06C04Z11/094/a1 B DALI 3000	IP40	3000	22	2970	2610		3,1	60
60041	LED-5L06C04Z11/094/a2 B DALI 3000	IP40	3000	22	2970	2610		3,1	60
60042	LED-5L06C04Z11/094/a3 B DALI 3000	IP40	3000	22	2970	2610		3,1	60
60043	LED-5L06C04Z11/094/a4 B DALI 3000	IP40	3000	22	2970	2610		3,1	60
60044	LED-5L06C04Z11/094/a5 B DALI 3000	IP40	3000	22	2970	2610		3,1	60
60540	LED-5L06C04Z11/094/a1 B DALI 4000	IP40	4000	22	3130	2760		3,1	60
60541	LED-5L06C04Z11/094/a2 B DALI 4000	IP40	4000	22	3130	2760		3,1	60
60542	LED-5L06C04Z11/094/a3 B DALI 4000	IP40	4000	22	3130	2760		3,1	60
60543	LED-5L06C04Z11/094/a4 B DALI 4000	IP40	4000	22	3130	2760		3,1	60
60544	LED-5L06C04Z11/094/a5 B DALI 4000	IP40	4000	22	3130	2760		3,1	60