



AURA 4

| | |
|-----------------------|---|
| Dimensions: | ø 420 mm |
| Color: | white |
| Type: | wall or ceiling mounted |
| Shade: | handmade three-layer glass TRIPLEX OPAL (matt finish) |
| Shade attach.: | two-step clamp holders |
| Fixture: | powder coated steel sheet (IP43) |
| Equipment: | STANDARD, LED |



Standard

| Code | Type | IP | Source | Input [W] | Socket | T [h] | m [kg] | Warranty [month] |
|---------------------------|-----------------------|------|--------|-----------|----------|-------|--------|------------------|
| Classic | | | | | | | | |
| 40086 | IN-22K74/072 | IP43 | | 2x75 | 2xE27 | | 3,5 | 24 |
| 40088 | E-26K74/072 | IP43 | | 2x26 | 2xG24q3 | | 3,7 | 24 |
| 42308 | E-26K74/072 32W | IP43 | | 2x32 | 2xGX24q3 | | 3,7 | 24 |
| Sensor | | | | | | | | |
| 46104 | IN-22K74/072 HF | IP43 | | 2x60 | 2xE27 | | 3,7 | 24 |
| Dimmable | | | | | | | | |
| 44015 | ES-26K74/072 DALI | IP43 | | 2x26 | 2xG24q3 | | 3,7 | 24 |
| 55310 | ES-26K74/072 32W DALI | IP43 | | 2x32 | 2xGX24q3 | | 3,7 | 24 |
| Emergency combined | | | | | | | | |
| 46202 | NKC-226/13/072 | IP43 | | 2x26 | 2xG24q3 | 1 | 4,0 | 24 |

LED

| Code | Type | IP | CCT [K] | Input [W] | Lum. flux of LED [lm] | Lum. flux of luminaire [lm] | T [h] | m [kg] | Warranty [month] |
|----------------|----------------------------|------|---------|-----------|-----------------------|-----------------------------|-------|--------|------------------|
| Classic | | | | | | | | | |
| 59021 | LED-1L15C07K75/072 3000 | IP43 | 3000 | 21 | 2770 | 2050 | | 2,8 | 60 |
| 59025 | LED-1L15B07K75/072 3000 | IP43 | 3000 | 29 | 3880 | 2870 | | 2,8 | 60 |
| 59521 | LED-1L15C07K75/072 4000 | IP43 | 4000 | 21 | 2920 | 2160 | | 2,8 | 60 |
| 59525 | LED-1L15B07K75/072 4000 | IP43 | 4000 | 29 | 4050 | 3000 | | 2,8 | 60 |
| Sensor | | | | | | | | | |
| 59022 | LED-1L15C07K75/072 HF 3000 | IP43 | 3000 | 21 | 2770 | 2050 | | 2,8 | 60 |
| 59026 | LED-1L15B07K75/072 HF 3000 | IP43 | 3000 | 29 | 3880 | 2870 | | 2,8 | 60 |
| 59522 | LED-1L15C07K75/072 HF 4000 | IP43 | 4000 | 21 | 2920 | 2160 | | 2,8 | 60 |

| Code | Type | IP | CCT [K] | Input [W] | Lum. flux of LED [lm] | Lum. flux of luminaire [lm] | T [h] | m [kg] | Warranty [month] |
|------------------------------------|--------------------------------------|------|---------|-----------|-----------------------|-----------------------------|-------|--------|------------------|
| 59526 | LED-1L15B07K75/072 HF 4000 | IP43 | 4000 | 29 | 4050 | 3000 | | 2,8 | 60 |
| Dimmable | | | | | | | | | |
| 59023 | LED-1L15C07K75/072 DALI 3000 | IP43 | 3000 | 21 | 2770 | 2050 | | 2,8 | 60 |
| 59027 | LED-1L15B07K75/072 DALI 3000 | IP43 | 3000 | 29 | 3880 | 2870 | | 2,8 | 60 |
| 59523 | LED-1L15C07K75/072 DALI 4000 | IP43 | 4000 | 21 | 2920 | 2160 | | 2,8 | 60 |
| 59527 | LED-1L15B07K75/072 DALI 4000 | IP43 | 4000 | 29 | 4050 | 3000 | | 2,8 | 60 |
| Emergency combined | | | | | | | | | |
| 59030 | LED-1L15C07K75/072/NK1W 3000 | IP43 | 3000 | 21 | 2770 | 2050 | 3 | 2,8 | 60 |
| 59032 | LED-1L15B07K75/072/NK1W 3000 | IP43 | 3000 | 29 | 3880 | 2870 | 3 | 2,8 | 60 |
| 59530 | LED-1L15C07K75/072/NK1W 4000 | IP43 | 4000 | 21 | 2920 | 2160 | 3 | 2,8 | 60 |
| 59532 | LED-1L15B07K75/072/NK1W 4000 | IP43 | 4000 | 29 | 4050 | 3000 | 3 | 2,8 | 60 |
| Emergency combined + sensor | | | | | | | | | |
| 59031 | LED-1L15C07K75/072/NK1W HF 3000 | IP43 | 3000 | 21 | 2770 | 2050 | 3 | 2,8 | 60 |
| 59033 | LED-1L15B07K75/072/NK1W HF 3000 | IP43 | 3000 | 29 | 3880 | 2870 | 3 | 2,8 | 60 |
| 59531 | LED-1L15C07K75/072/NK1W HF 4000 | IP43 | 4000 | 21 | 2920 | 2160 | 3 | 2,8 | 60 |
| 59533 | LED-1L15B07K75/072/NK1W HF 4000 | IP43 | 4000 | 29 | 4050 | 3000 | 3 | 2,8 | 60 |
| Two-circuits | | | | | | | | | |
| 59029 | LED-1L15C07K75/072 2/1 3000 | IP43 | 3000 | 29 | 3880 | 2870 | | 2,8 | 60 |
| 59529 | LED-1L15C07K75/072 2/1 4000 | IP43 | 4000 | 29 | 4050 | 3000 | | 2,8 | 60 |
| Corridor | | | | | | | | | |
| 59024 | LED-1L15C07K75/072 DALI HF CORR 3000 | IP43 | 3000 | 21 | 2770 | 2050 | | 2,8 | 60 |
| 59028 | LED-1L15B07K75/072 DALI HF CORR 3000 | IP43 | 3000 | 29 | 3880 | 2870 | | 2,8 | 60 |
| 59524 | LED-1L15C07K75/072 DALI HF CORR 4000 | IP43 | 4000 | 21 | 2920 | 2160 | | 2,8 | 60 |
| 59528 | LED-1L15B07K75/072 DALI HF CORR 4000 | IP43 | 4000 | 29 | 4050 | 3000 | | 2,8 | 60 |