



TITAN 2 - PMMA

Dimensions:	ø 400 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polymethylmetacrylate (PMMA)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56018	IN-22KN83/PM08	IP44		2x40	2xE27		1,4	24
56019	E-26KN83/PM08	IP44		2x26	2xG24q3		1,5	24
Sensor								
46130	IN-22KN83/PM08 HF	IP44		2x40	2xE27		1,5	24
Emergency combined								
46214	NKC-226/13/PM08	IP44		2x26	2xG24q3	1	1,9	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56224	LED-1L16C07KN83/PM08 3000	IP54	3000	28	3690	2550		1,8	60
53267	LED-1L16B07KN83/PM08 3000	IP54	3000	36	4850	3200		1,8	60
56724	LED-1L16C07KN83/PM08 4000	IP54	4000	28	3890	2680		1,8	60
53767	LED-1L16B07KN83/PM08 4000	IP54	4000	36	5070	3500		1,8	60
Sensor									
56225	LED-1L16C07KN83/PM08 HF 3000	IP54	3000	28	3690	2550		1,8	60
53273	LED-1L16B07KN83/PM08 HF 3000	IP54	3000	36	4850	3200		1,8	60
56725	LED-1L16C07KN83/PM08 HF 4000	IP54	4000	28	3890	2680		1,8	60
53773	LED-1L16B07KN83/PM08 HF 4000	IP54	4000	36	5070	3500		1,8	60
Dimmable									
56226	LED-1L16C07KN83/PM08 DALI 3000	IP54	3000	28	3690	2550		1,8	60
53271	LED-1L16B07KN83/PM08 DALI 3000	IP54	3000	36	4850	3200		1,8	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
56726	LED-1L16C07KN83/PM08 DALI 4000	IP54	4000	28	3890	2680		1,8	60
53771	LED-1L16B07KN83/PM08 DALI 4000	IP54	4000	36	5070	3500		1,8	60
Emergency combined									
56229	LED-1L16C07KN83/PM08/NK1W 3000	IP54	3000	28	3690	2550	3	1,8	60
53275	LED-1L16B07KN83/PM08/NK1W 3000	IP54	3000	36	4850	3200	3	1,8	60
56729	LED-1L16C07KN83/PM08/NK1W 4000	IP54	4000	28	3890	2680	3	1,8	60
53775	LED-1L16B07KN83/PM08/NK1W 4000	IP54	4000	36	5070	3500	3	1,8	60
Emergency combined + sensor									
56230	LED-1L16C07KN83/PM08/NK1W HF 3000	IP54	3000	28	3690	2550	3	1,8	60
56231	LED-1L16B07KN83/PM08/NK1W HF 3000	IP54	3000	36	4850	3200	3	1,8	60
56730	LED-1L16C07KN83/PM08/NK1W HF 4000	IP54	4000	28	3890	2680	3	1,8	60
56731	LED-1L16B07KN83/PM08/NK1W HF 4000	IP54	4000	36	5070	3500	3	1,8	60
Two-circuits									
53269	LED-1L16B07KN83/PM08 2/1 3000	IP54	3000	36	4850	3200		1,8	60
53769	LED-1L16B07KN83/PM08 2/1 4000	IP54	4000	36	5070	3500		1,8	60
Corridor									
56227	LED-1L16C07KN83/PM08 DALI HF CORR 3000	IP54	3000	28	3690	2550		1,8	60
56228	LED-1L16B07KN83/PM08 DALI HF CORR 3000	IP54	3000	36	4850	3200		1,8	60
56727	LED-1L16C07KN83/PM08 DALI HF CORR 4000	IP54	4000	28	3890	2680		1,8	60
56728	LED-1L16B07KN83/PM08 DALI HF CORR 4000	IP54	4000	36	5070	3500		1,8	60