


# TILIA 1A

<b>Dimensions:</b>	220x220 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	opal polycarbonate (PC)
<b>Shade attach.:</b>	two-step clamp holders
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
52120	IN-12NU1/PC31	IP44		20	E27		0,0	

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
56350	LED-1L31C03NU1/PC31 3000	IP44	3000	11	1380	980		0,0	60
56850	LED-1L31C03NU1/PC31 4000	IP44	4000	11	1460	1040		0,0	60
<b>Sensor</b>									
56351	LED-1L31C03NU1/PC31 HF 3000	IP44	3000	11	1380	980		0,0	60
56851	LED-1L31C03NU1/PC31 HF 4000	IP44	4000	11	1460	1040		0,0	60
<b>Dimmable</b>									
56352	LED-1L31C03NU1/PC31 DALI 3000	IP44	3000	11	1380	980		0,0	60
56852	LED-1L31C03NU1/PC31 DALI 4000	IP44	4000	11	1460	1040		0,0	60