



DELIA 3 - PMMA

Dimensions:	ø 500 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polymethylmetacrylate (PMMA)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56143	IN-32KN94/PM24	IP44		3x30	3xE27		2,5	24
56144	E-26KN94/PM24 32W	IP44		2x32	2xGX24q3		2,9	24
56145	E-27KN94/PM24	IP44		2x36	2xG10		2,9	24
Sensor								
56149	IN-32KN94/PM24 HF	IP44		3x30	3xE27		3,0	24
Emergency combined								
56154	NKC-232/16/PM24	IP44		2x32	2xGX24q3	1	3,2	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56330	LED-3L53C07KN94/PM24 3000	IP54	3000	35	4750	3140		2,6	60
56334	LED-3L53C10KN94/PM24 3000	IP54	3000	53	6780	4470		2,6	60
56830	LED-3L53C07KN94/PM24 4000	IP54	4000	35	5010	3310		2,6	60
56834	LED-3L53C10KN94/PM24 4000	IP54	4000	53	7150	4720		2,6	60
Dimmable									
56332	LED-3L53C07KN94/PM24 DALI 3000	IP54	3000	35	4750	3140		2,6	60
56336	LED-3L53C10KN94/PM24 DALI 3000	IP54	3000	53	6780	4470		2,6	60
56832	LED-3L53C07KN94/PM24 DALI 4000	IP54	4000	35	5010	3310		2,6	60
56836	LED-3L53C10KN94/PM24 DALI 4000	IP54	4000	53	7150	4720		2,6	60
Emergency combined									
56338	LED-3L53C07KN94/PM24/NK1W 3000	IP54	3000	35	4750	3140	3	2,6	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
56339	LED-3L53C10KN94/PM24/NK1W 3000	IP54	3000	53	6780	4470	3	2,6	60
56838	LED-3L53C07KN94/PM24/NK1W 4000	IP54	4000	35	5010	3310	3	2,6	60
56839	LED-3L53C10KN94/PM24/NK1W 4000	IP54	4000	53	7150	4720	3	2,6	60