



DELIA 1 - PC

Dimensions:	ø 300 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polycarbonate (PC)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56075	IN-12KN62/PC22	IP44		40	E27		0,8	24
56076	E-16KN62/PC22	IP44		26	G24q3		1,0	24
56078	E-25KN62/PC22	IP44		2x18	2xG24q2		1,1	24
Sensor								
56079	IN-12KN62/PC22 HF	IP44		40	E27		0,9	24
Emergency combined								
56082	NK-E-26/PC22	IP44		26	G24q3	1	1,4	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56290	LED-1L14C03KN62/PC22 3000	IP54	3000	15	2000	1480		1,0	60
53316	LED-1L14B07KN62/PC22 3000	IP54	3000	20	2590	1920		1,1	60
56790	LED-1L14C03KN62/PC22 4000	IP54	4000	15	2110	1560		1,0	60
53816	LED-1L14B07KN62/PC22 4000	IP54	4000	20	2700	2000		1,1	60
Sensor									
56291	LED-1L14C03KN62/PC22 HF 3000	IP54	3000	15	2000	1480		1,0	60
53320	LED-1L14B07KN62/PC22 HF 3000	IP54	3000	20	2590	1920		1,1	60
56791	LED-1L14C03KN62/PC22 HF 4000	IP54	4000	15	2110	1560		1,0	60
53820	LED-1L14B07KN62/PC22 HF 4000	IP54	4000	20	2700	2000		1,1	60
Dimmable									
56292	LED-1L14C03KN62/PC22 DALI 3000	IP54	3000	15	2000	1480		1,0	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
53318	LED-1L14B07KN62/PC22 DALI 3000	IP54	3000	20	2590	1920		1,1	60
56792	LED-1L14C03KN62/PC22 DALI 4000	IP54	4000	15	2110	1560		1,0	60
53818	LED-1L14B07KN62/PC22 DALI 4000	IP54	4000	20	2700	2000		1,1	60
Emergency combined									
56293	LED-1L14C03KN62/PC22/NK1W 3000	IP54	3000	15	2000	1480	3	1,0	60
53322	LED-1L14B07KN62/PC22/NK1W 3000	IP54	3000	20	2590	1920	3	1,1	60
56793	LED-1L14C03KN62/PC22/NK1W 4000	IP54	4000	15	2110	1560	3	1,0	60
53822	LED-1L14B07KN62/PC22/NK1W 4000	IP54	4000	20	2700	2000	3	1,1	60
Emergency combined + sensor									
53324	LED-1L14B07KN62/PC22/NK1W HF 3000	IP54	3000	20	2590	1920	3	1,1	60
56294	LED-1L14C03KN62/PC22/NK1W HF 3000	IP54	3000	15	2000	1480	3	1,0	60
56794	LED-1L14C03KN62/PC22/NK1W HF 4000	IP54	4000	15	2110	1560	3	1,0	60
53824	LED-1L14B07KN62/PC22/NK1W HF 4000	IP54	4000	20	2700	2000	3	1,1	60