



ELSA 2

Dimensions:	ø 300 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	bayonet
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
44726	IN-12B13/025	IP20		100	E27		1,7	24
44727	IN-22B13/025	IP20		2x60	2xE27		1,8	24
44732	E-16B13/025	IP20		26	G24q3		2,0	24
44734	E-25B13/025	IP20		2x18	2xG24q2		2,1	24
44740	IN-12BT13/025	IP44		100	E27		1,7	24
44741	IN-22BT13/025	IP44		2x60	2xE27		1,9	24
44746	E-16BT13/025	IP44		26	G24q3		2,1	24
44748	E-25BT13/025	IP44		2x18	2xG24q2		2,2	24
Sensor								
44735	IN-12B13/025 HF	IP20		60	E27		1,8	24
44736	E-16B13/025 HF	IP20		26	G24q3		2,0	24
44749	IN-12BT13/025 HF	IP44		60	E27		1,9	24
44750	E-16BT13/025 HF	IP44		26	G24q3		2,1	24
Emergency combined								
44738	NK-E-13/025	IP20		13	G24q1	1	2,3	24
44752	NK-E-13/T/025	IP44		13	G24q1	1	2,4	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
59070	LED-1L18C02BT13/025 3000	IP44	3000	11	1450	1060		2,1	60
59445	LED-1L18C03BT13/025 3000	IP44	3000	15	1950	1420		2,1	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
59570	LED-1L18C02BT13/025 4000	IP44	4000	11	1530	1120		2,1	60
59945	LED-1L18C03BT13/025 4000	IP44	4000	15	2050	1500		2,1	60
Sensor									
59071	LED-1L18C02BT13/025 HF 3000	IP44	3000	11	1450	1060		2,1	60
59446	LED-1L18C03BT13/025 HF 3000	IP44	3000	15	1950	1420		2,1	60
59571	LED-1L18C02BT13/025 HF 4000	IP44	4000	11	1530	1120		2,1	60
59946	LED-1L18C03BT13/025 HF 4000	IP44	4000	15	2050	1500		2,1	60
Dimmable									
59072	LED-1L18C02BT13/025 DALI 3000	IP44	3000	11	1450	1060		2,1	60
59447	LED-1L18C03BT13/025 DALI 3000	IP44	3000	15	1950	1420		2,1	60
59572	LED-1L18C02BT13/025 DALI 4000	IP44	4000	11	1530	1120		2,1	60
59947	LED-1L18C03BT13/025 DALI 4000	IP44	4000	15	2050	1500		2,1	60
Emergency combined									
59075	LED-1L18C02BT13/025/NK1W 3000	IP44	3000	11	1450	1060	3	2,1	60
59449	LED-1L18C03BT13/025/NK1W 3000	IP44	3000	15	1950	1420	3	2,1	60
59575	LED-1L18C02BT13/025/NK1W 4000	IP44	4000	11	1530	1120	3	2,1	60
59949	LED-1L18C03BT13/025/NK1W 4000	IP44	4000	15	2050	1500	3	2,1	60
Corridor									
59073	LED-1L18C02BT13/025 DALI HF CORR 3000	IP44	3000	11	1450	1060		2,1	60
59448	LED-1L18C03BT13/025 DALI HF CORR 3000	IP44	3000	15	1950	1420		2,1	60
59573	LED-1L18C02BT13/025 DALI HF CORR 4000	IP44	4000	11	1530	1120		2,1	60
59948	LED-1L18C03BT13/025 DALI HF CORR 4000	IP44	4000	15	2050	1500		2,1	60