



DELIA 1 - PMMA

Dimensions:	ø 300 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polymethylmetacrylate (PMMA)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56083	IN-12KN62/PM22	IP44		30	E27		0,8	24
56084	E-16KN62/PM22	IP44		26	G24q3		1,0	24
56086	E-25KN62/PM22	IP44		2x18	2xG24q2		1,1	24
Sensor								
56087	IN-12KN62/PM22 HF	IP44		30	E27		0,9	24
Emergency combined								
56090	NK-E-26/PM22	IP44		26	G24q3	1	1,4	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56295	LED-1L14C03KN62/PM22 3000	IP54	3000	15	2000	1440		1,0	60
53326	LED-1L14B07KN62/PM22 3000	IP54	3000	20	2590	1860		1,1	60
56795	LED-1L14C03KN62/PM22 4000	IP54	4000	15	2110	1520		1,0	60
53826	LED-1L14B07KN62/PM22 4000	IP54	4000	20	2700	1940		1,1	60
Sensor									
56296	LED-1L14C03KN62/PM22 HF 3000	IP54	3000	15	2000	1440		1,0	60
53330	LED-1L14B07KN62/PM22 HF 3000	IP54	3000	20	2590	1860		1,1	60
56796	LED-1L14C03KN62/PM22 HF 4000	IP54	4000	15	2110	1520		1,0	60
53830	LED-1L14B07KN62/PM22 HF 4000	IP54	4000	20	2700	1940		1,1	60
Dimmable									
56297	LED-1L14C03KN62/PM22 DALI 3000	IP54	3000	15	2000	1440		1,0	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
53328	LED-1L14B07KN62/PM22 DALI 3000	IP54	3000	20	2590	1860		1,1	60
56797	LED-1L14C03KN62/PM22 DALI 4000	IP54	4000	15	2110	1520		1,0	60
53828	LED-1L14B07KN62/PM22 DALI 4000	IP54	4000	20	2700	1940		1,1	60
Emergency combined									
56298	LED-1L14C03KN62/PM22/NK1W 3000	IP54	3000	15	2000	1440	3	1,0	60
53332	LED-1L14B07KN62/PM22/NK1W 3000	IP54	3000	20	2590	1860	3	1,1	60
56798	LED-1L14C03KN62/PM22/NK1W 4000	IP54	4000	15	2110	1520	3	1,0	60
53832	LED-1L14B07KN62/PM22/NK1W 4000	IP54	4000	20	2700	1940	3	1,1	60
Emergency combined + sensor									
56299	LED-1L14C03KN62/PM22/NK1W HF 3000	IP54	3000	15	2000	1440	3	1,0	60
53334	LED-1L14B07KN62/PM22/NK1W HF 3000	IP54	3000	20	2590	1860	3	1,1	60
56799	LED-1L14C03KN62/PM22/NK1W HF 4000	IP54	4000	15	2110	1520	3	1,0	60
53834	LED-1L14B07KN62/PM22/NK1W HF 4000	IP54	4000	20	2700	1940	3	1,1	60