



TITAN 2 - PC

Dimensions:	ø 400 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polycarbonate (PC)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56012	IN-22KN83/PC08	IP44		2x60	2xE27		1,4	24
56013	E-26KN83/PC08	IP44		2x26	2xG24q3		1,5	24
Sensor								
46129	IN-22KN83/PC08 HF	IP44		2x40	2xE27		0,8	24
Emergency combined								
46213	NKC-226/13/PC08	IP44		2x26	2xG24q3	1	1,9	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56216	LED-1L16C07KN83/PC08 3000	IP54	3000	28	3690	2440		1,6	60
53256	LED-1L16B07KN83/PC08 3000	IP54	3000	36	4850	3200		1,8	60
56716	LED-1L16C07KN83/PC08 4000	IP54	4000	28	3890	2570		1,6	60
53756	LED-1L16B07KN83/PC08 4000	IP54	4000	36	5070	3350		1,8	60
Sensor									
56217	LED-1L16C07KN83/PC08 HF 3000	IP54	3000	28	3690	2440		1,6	60
53262	LED-1L16B07KN83/PC08 HF 3000	IP54	3000	36	4850	3200		1,8	60
56717	LED-1L16C07KN83/PC08 HF 4000	IP54	4000	28	3890	2570		1,6	60
53762	LED-1L16B07KN83/PC08 HF 4000	IP54	4000	36	5070	3350		1,8	60
Dimmable									
56218	LED-1L16C07KN83/PC08 DALI 3000	IP54	3000	28	3690	2440		1,6	60
53260	LED-1L16B07KN83/PC08 DALI 3000	IP54	3000	36	4850	3200		1,8	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
56718	LED-1L16C07KN83/PC08 DALI 4000	IP54	4000	28	3890	2570		1,6	60
53760	LED-1L16B07KN83/PC08 DALI 4000	IP54	4000	36	5070	3350		1,8	60
Emergency combined									
56221	LED-1L16C07KN83/PC08/NK1W 3000	IP54	3000	28	3690	2440	3	1,6	60
53264	LED-1L16B07KN83/PC08/NK1W 3000	IP54	3000	36	4850	3200	3	1,8	60
56721	LED-1L16C07KN83/PC08/NK1W 4000	IP54	4000	28	3890	2570	3	1,6	60
53764	LED-1L16B07KN83/PC08/NK1W 4000	IP54	4000	36	5070	3350	3	1,8	60
Emergency combined + sensor									
56222	LED-1L16C07KN83/PC08/NK1W HF 3000	IP54	3000	28	3690	2440	3	1,6	60
56223	LED-1L16B07KN83/PC08/NK1W HF 3000	IP54	3000	36	4850	3200	3	1,8	60
56722	LED-1L16C07KN83/PC08/NK1W HF 4000	IP54	4000	28	3890	2570	3	1,6	60
56723	LED-1L16B07KN83/PC08/NK1W HF 4000	IP54	4000	36	5070	3350	3	1,8	60
Two-circuits									
53258	LED-1L16B07KN83/PC08 2/1 3000	IP54	3000	36	4850	3200		1,8	60
53758	LED-1L16B07KN83/PC08 2/1 4000	IP54	4000	36	5070	3350		1,8	60
Corridor									
56219	LED-1L16C07KN83/PC08 DALI HF CORR 3000	IP54	3000	28	3690	2440		1,6	60
56220	LED-1L16B07KN83/PC08 DALI HF CORR 3000	IP54	3000	36	4850	3200		1,8	60
56719	LED-1L16C07KN83/PC08 DALI HF CORR 4000	IP54	4000	28	3890	2570		1,6	60
56720	LED-1L16B07KN83/PC08 DALI HF CORR 4000	IP54	4000	36	5070	3350		1,8	60