



TITAN 3 - PMMA

Dimensions:	ø 500 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polymethylmetacrylate (PMMA)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56030	IN-32KN94/PM09	IP44		3x40	3xE27		2,0	24
44643	E-26KN94/PM09 32W	IP44		2x32	2xGX24q3		2,1	24
56031	E-27KN94/PM09	IP44		2x36	2xG10		2,1	24
Sensor								
46132	IN-32KN94/PM09 HF	IP44		3x40	3xE27		2,1	24
Emergency combined								
44644	NKC-232/16/PM09	IP44		2x32	2xGX24q3	1	2,5	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56245	LED-2L43C07KN94/PM09 3000	IP54	3000	37	5050	3490		2,8	60
56249	LED-2L43C10KN94/PM09 3000	IP54	3000	56	7250	5000		2,8	60
56745	LED-2L43C07KN94/PM09 4000	IP54	4000	37	5330	3680		2,8	60
56749	LED-2L43C10KN94/PM09 4000	IP54	4000	56	7640	5270		2,8	60
Sensor									
56246	LED-2L43C07KN94/PM09 HF 3000	IP54	3000	37	5050	3490		2,8	60
56250	LED-2L43C10KN94/PM09 HF 3000	IP54	3000	56	7250	5000		2,8	60
56746	LED-2L43C07KN94/PM09 HF 4000	IP54	4000	37	5330	3680		2,8	60
56750	LED-2L43C10KN94/PM09 HF 4000	IP54	4000	56	7640	5270		2,8	60
Dimmable									
56247	LED-2L43C07KN94/PM09 DALI 3000	IP54	3000	37	5050	3490		2,8	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
56251	LED-2L43C10KN94/PM09 DALI 3000	IP54	3000	56	7250	5000		2,8	60
56747	LED-2L43C07KN94/PM09 DALI 4000	IP54	4000	37	5330	3680		2,8	60
56751	LED-2L43C10KN94/PM09 DALI 4000	IP54	4000	56	7640	5270		2,8	60
Emergency combined									
56253	LED-2L43C07KN94/PM09/NK1W 3000	IP54	3000	37	5050	3490	3	2,8	60
56254	LED-2L43C10KN94/PM09/NK1W 3000	IP54	3000	56	7250	5000	3	2,8	60
56753	LED-2L43C07KN94/PM09/NK1W 4000	IP54	4000	37	5330	3680	3	2,8	60
56754	LED-2L43C10KN94/PM09/NK1W 4000	IP54	4000	56	7640	5270	3	2,8	60
Corridor									
56248	LED-2L43C07KN94/PM09 DALI HF CORR 3000	IP54	3000	37	5050	3490		2,8	60
56252	LED-2L43C10KN94/PM09 DALI HF CORR 3000	IP54	3000	56	7250	5000		2,8	60
56748	LED-2L43C07KN94/PM09 DALI HF CORR 4000	IP54	4000	37	5330	3680		2,8	60
56752	LED-2L43C10KN94/PM09 DALI HF CORR 4000	IP54	4000	56	7640	5270		2,8	60