


TITAN 4

Dimensions:	ø 650 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polymethylmetacrylate (PMMA)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56056	IN-42KN10/PM10	IP44		4x40	4xE27		3,6	24
56058	E-47KN10/PM10	IP44		4x36	4x2G10		4,1	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56260	LED-6L51B07KN10/PM10 3000	IP54	3000	68	10210	6740		5,8	60
56263	LED-6L51B09KN10/PM10 3000	IP54	3000	94	13440	8870		5,4	60
56760	LED-6L51B07KN10/PM10 4000	IP54	4000	68	10670	7040		5,8	60
56763	LED-6L51B09KN10/PM10 4000	IP54	4000	94	14040	9270		5,4	60
Dimmable									
56261	LED-6L51B07KN10/PM10 DALI 3000	IP54	3000	68	10210	6740		5,8	60
56264	LED-6L51B09KN10/PM10 DALI 3000	IP54	3000	94	13440	8870		5,4	60
56761	LED-6L51B07KN10/PM10 DALI 4000	IP54	4000	68	10670	7040		5,8	60
56764	LED-6L51B09KN10/PM10 DALI 4000	IP54	4000	94	14040	9270		5,4	60
Two-circuits									
56262	LED-6L51B07KN10/PM10 2/1 3000	IP54	3000	68	10210	6740		5,8	60
56265	LED-6L51B09KN10/PM10 2/1 3000	IP54	3000	94	13440	8870		5,4	60
56762	LED-6L51B07KN10/PM10 2/1 4000	IP54	4000	68	10670	7040		5,8	60
56765	LED-6L51B09KN10/PM10 2/1 4000	IP54	4000	94	14040	9270		5,4	60