

OPPOSITE 2

indoor lighting

ES-SYSTEM
Light is Life

Luminaire for recessed installation in ceilings or ceiling grids
 BODY: painted aluminum sheet, white painted steel frame; a version for 625x625mm ceilings also possible
 DIFFUSER: microprismatic PMMA,
 UGRPOWER SUPPLY: remote electronic ballast
 3xS TECHNOLOGY: save money, save energy, save time



Concave microprismatic PMMA diffuser, DALI version, white, 81° light distribution, UGR <19

5950061	OPPOSITE 2 IN 597	LED 3000K	4100 lm	230V AC	46W	5.50
5950461	OPPOSITE 2 IN 622	LED 3000K	4100 lm	230V AC	46W	5.60
5951061	OPPOSITE 2 IN 597	LED 4000K	4100 lm	230V AC	46W	5.50
5951461	OPPOSITE 2 IN 622	LED 4000K	4100 lm	230V AC	46W	5.60

Concave microprismatic PMMA diffuser, ON/OFF version, white, 81° light distribution, UGR <19

5950001	OPPOSITE 2 IN 597	LED 3000K	4100 lm	230V AC	46W	5.50
5950401	OPPOSITE 2 IN 622	LED 3000K	4100 lm	230V AC	46W	5.60
5951001	OPPOSITE 2 IN 597	LED 4000K	4100 lm	230V AC	46W	5.50
5951401	OPPOSITE 2 IN 622	LED 4000K	4100 lm	230V AC	46W	5.60

Convex microprismatic PMMA diffuser, DALI version, white, 81° light distribution, UGR <19

5948061	OPPOSITE 2 OUT 597	LED 3000K	4100 lm	230V AC	46W	5.00
5948461	OPPOSITE 2 OUT 622	LED 3000K	4100 lm	230V AC	46W	5.10

5949061	OPPOSITE 2 OUT 597	LED 4000K	4100 lm	230V AC	46W	5.00
5949461	OPPOSITE 2 OUT 622	LED 4000K	4100 lm	230V AC	46W	5.10

Convex microprismatic PMMA diffuser, ON/OFF version, white, 81° light distribution, UGR <19

5948001	OPPOSITE 2 OUT 597	LED 3000K	4100 lm	230V AC	46W	5.00
5948401	OPPOSITE 2 OUT 622	LED 3000K	4100 lm	230V AC	46W	5.10
5949001	OPPOSITE 2 OUT 597	LED 4000K	4100 lm	230V AC	46W	5.00
5949401	OPPOSITE 2 OUT 622	LED 4000K	4100 lm	230V AC	46W	5.10