



Saves Your Energy

## PRODUCT CARD

9.2.2016

1/3

# AVD550.139L/3K


Name: **Universal luminaire**  
AVD550 LED 39W/830 PC O

Type: AVD550.139L/3K

GTIN: 6438389000030

Package: 1/0

Unit: PCS



## Technical specification

### Electrical values

Electronic control gear x

Power factor (cos f) 0.94

Voltage 230 V

### Ratings

Rated voltage 230 V

Degree of protection IP21

Rated frequency 50/60 Hz

Protection class I

ETIM class Ceiling-/wall luminaire

### Mechanical

Impact strength IK09

### Dimensions

Length 550 mm

Height 105 mm

Width 550 mm

### Temperatures

Operating temperature -20 ... 25 °C

### Features

Light source LED 39W/830

With light source Colour scheme 830

### Materials

Material Aluminium

### STK

Dimmability No

Lamp base LED-mod

Light source qty and power (W) 1x39

Light source (ILCOS) DS

Light source LED

Ensto Finland Oy

Ensio Miettisen katu 2  
P.O.Box 77  
06101 Porvoo, Finland

Tel. +358 204 76 21  
Fax +358 204 76 2750

[www.ensto.com](http://www.ensto.com)



# AVD550.139L/3K

## Materials

Optics	Opal diffuser
Installation	Surface/Recess
Cut out diameter (mm)	485
Recess depth	30 mm
IN-OUT- looping	Continuous
Electrical connection, cable size	5x2,5
Electrical connection, connector type	Pushwire terminal
Colour temperature	3000 K
Color rendering index	Ra>80
LED-luminaire luminous flux	3890 lm
LED-module lifetime (L70)	50000 h
Connected load	39 W
LED-module changeability	No
LED-luminaire efficacy	100 lm/W

## ETIM

Suitable for suspended mounting	x
Suitable for ceiling mounting	x
Suitable for built-in mounting	x
Suitable for surface mounting	x
Lamp type	LED not exchangeable
With lamp	x
Lamp holder	None
Suitable for number of lamps	1
Lamp power	39 W
Lamp power at multiwatt	Not applicable
Type of control gear	LED operating device current-controlled
Control gear included	x
Type of dimming	Not dimmable
Circuit	Parallel-compensated
Suitable for emergency lighting	
Emergency unit integrated	
Nominal voltage	230 V
Colour temperature	≥ 3000 K
Material housing	Aluminium
Type of surface	Matt
Colour housing	White
Suitable for light line configuration	
Material cover	Plastic, opal
Fit for monitor workplace	
Type of grid	None



Saves Your Energy

## PRODUCT CARD

9.2.2016

3/3

# AVD550.139L/3K

Reflector	None
Light sharing	Symmetric
Radiation angle	Open beam
Light outlet	Direct
Length	550 mm
Width	550 mm
Height/depth	105 mm
Built-in height/depth	30 mm
Built-in diameter	485 mm
With movement sensor	
With light sensor	
Protection class	I
Degree of protection (IP)	IP21
Impact strength	IK09
Build in insulated ceiling, fire-resistance "F with roof"	x
Ambient temperature	-20 ... 25 °C
Filament test according to IEC 60695-2-10	None
System power	39 W
Voltage type	AC
Effective luminous flux	3890 lm
Colour of light	White
Colour rendering index CRI	80-89

Ensto Finland Oy

Ensio Miettisen katu 2  
P.O.Box 77  
06101 Porvoo, Finland

Tel. +358 204 76 21  
Fax +358 204 76 2750

[www.ensto.com](http://www.ensto.com)