


ELSA 6

Dimensions:	ø 590 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	bayonet
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
54976	IN-32B17/627	IP20		3x75	3xE27		6,4	24
54979	E-46B17/627	IP20		4x26	4xG24q3		7,2	24
54987	IN-32BT17/627	IP44		3x75	3xE27		6,4	24
54990	E-46BT17/627	IP44		4x26	4xG24q3		7,2	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
59098	LED-3L53C07BT17/627 3000	IP44	3000	35	4750	3090		7,6	60
59100	LED-3L53C10BT17/627 3000	IP44	3000	53	6780	4410		7,6	60
59598	LED-3L53C07BT17/627 4000	IP44	4000	35	5010	3260		7,6	60
59600	LED-3L53C10BT17/627 4000	IP44	4000	53	7150	4650		7,6	60
Dimmable									
59099	LED-3L53C07BT17/627 DALI 3000	IP44	3000	35	4750	3090		7,6	60
59101	LED-3L53C10BT17/627 DALI 3000	IP44	3000	53	6780	4410		7,6	60
59599	LED-3L53C07BT17/627 DALI 4000	IP44	4000	35	5010	3260		7,6	60
59601	LED-3L53C10BT17/627 DALI 4000	IP44	4000	53	7150	4650		7,6	60
Emergency combined									
59102	LED-3L53C07BT17/627/NK1W 3000	IP44	3000	35	4750	3090	3	7,6	60
59103	LED-3L53C10BT17/627/NK1W 3000	IP44	3000	53	6780	4410	3	7,6	60
59602	LED-3L53C07BT17/627/NK1W 4000	IP44	4000	35	5010	3260	3	7,6	60
59603	LED-3L53C10BT17/627/NK1W 4000	IP44	4000	53	7150	4650	3	7,6	60