


AURA 9

Dimensions:	ø 590 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet (IP43)
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
42400	IN-32K98/084	IP43		3x75	3xE27		5,8	24
42404	E-46K98/084	IP43		4x26	4xG24q3		6,7	24
42409	E-46K98/084 32W	IP43		4x32	4xGX24q3		6,7	24
Dimmable								
42556	ES-46K98/084 DALI	IP43		4x26	4xG24q3		6,7	24
Emergency combined								
46205	NKC-242/16/084	IP43		2x42	2xGX24q4	1	7,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
59243	LED-2L43C07K98/084 3000	IP43	3000	37	5050	3490		7,0	60
59245	LED-2L43C10K98/084 3000	IP43	3000	56	7250	5000		7,0	60
59743	LED-2L43C07K98/084 4000	IP43	4000	37	5330	3680		7,0	60
59745	LED-2L43C10K98/084 4000	IP43	4000	56	7640	5270		7,0	60
Dimmable									
59244	LED-2L43C07K98/084 DALI 3000	IP43	3000	37	5050	3490		7,0	60
59246	LED-2L43C10K98/084 DALI 3000	IP43	3000	56	7250	5000		7,0	60
59744	LED-2L43C07K98/084 DALI 4000	IP43	4000	37	5330	3680		7,0	60
59746	LED-2L43C10K98/084 DALI 4000	IP43	4000	56	7640	5270		7,0	60
Emergency combined									
59247	LED-2L43C07K98/084/NK1W 3000	IP43	3000	37	5050	3490	3	7,0	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
59248	LED-2L43C10K98/084/NK1W 3000	IP43	3000	56	7250	5000	3	7,0	60
59747	LED-2L43C07K98/084/NK1W 4000	IP43	4000	37	5330	3680	3	7,0	60
59748	LED-2L43C10K98/084/NK1W 4000	IP43	4000	56	7640	5270	3	7,0	60