


# TITAN 1A - PC

<b>Dimensions:</b>	ø 220 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	opal polycarbonate (PC)
<b>Shade attach.:</b>	two-step clamp holders
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
56050	IN-12KN32/PC03	IP44		60	E27		0,5	24
<b>Sensor</b>								
52110	IN-12KN32/PC03 HF	IP44		40	E27		0,5	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
56200	LED-1L12C03KN32/PC03 3000	IP54	3000	9	1080	760		0,7	60
53231	LED-1L12B07KN32/PC03 3000	IP54	3000	11	1290	900		0,7	60
56700	LED-1L12C03KN32/PC03 4000	IP54	4000	9	1140	800		0,7	60
53731	LED-1L12B07KN32/PC03 4000	IP54	4000	11	1350	950		0,7	60
<b>Emergency</b>									
49002	LED-NZ1W/PC03 4000	IP54	4000	1	150	110	3	1,1	60
<b>Sensor</b>									
56201	LED-1L12C03KN32/PC03 HF 3000	IP54	3000	9	1080	760		0,7	60
56202	LED-1L12B07KN32/PC03 HF 3000	IP54	3000	11	1290	900		0,7	60
56701	LED-1L12C03KN32/PC03 HF 4000	IP54	4000	9	1140	800		0,7	60
56702	LED-1L12B07KN32/PC03 HF 4000	IP54	4000	11	1350	950		0,7	60