



TITAN 1 - PMMA

Dimensions:	ø 300 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polymethylmetacrylate (PMMA)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56006	IN-12KN62/PM06	IP44		40	E27		0,7	24
56007	E-16KN62/PM06	IP44		26	G24q3		0,8	24
56041	E-25KN62/PM06	IP44		2x18	2xG24q2		0,9	24
Sensor								
46128	IN-12KN62/PM06 HF	IP44		40	E27		0,8	24
Emergency combined								
46299	NK-E-26/PM06	IP44		26	G24q3	1	1,1	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56211	LED-1L14C03KN62/PM06 3000	IP54	3000	15	2000	1420		0,9	60
53245	LED-1L14B07KN62/PM06 3000	IP54	3000	20	2590	1840		0,9	60
56711	LED-1L14C03KN62/PM06 4000	IP54	4000	15	2110	1500		0,9	60
53745	LED-1L14B07KN62/PM06 4000	IP54	4000	20	2700	1920		0,9	60
Sensor									
56212	LED-1L14C03KN62/PM06 HF 3000	IP54	3000	15	2000	1420		0,9	60
53249	LED-1L14B07KN62/PM06 HF 3000	IP54	3000	20	2590	1840		0,9	60
56712	LED-1L14C03KN62/PM06 HF 4000	IP54	4000	15	2110	1500		0,9	60
53749	LED-1L14B07KN62/PM06 HF 4000	IP54	4000	20	2700	1920		0,9	60
Dimmable									
56213	LED-1L14C03KN62/PM06 DALI 3000	IP54	3000	15	2000	1420		0,9	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
53247	LED-1L14B07KN62/PM06 DALI 3000	IP54	3000	20	2590	1840		0,9	60
56713	LED-1L14C03KN62/PM06 DALI 4000	IP54	4000	15	2110	1500		0,9	60
53747	LED-1L14B07KN62/PM06 DALI 4000	IP54	4000	20	2700	1920		0,9	60
Emergency combined									
56214	LED-1L14C03KN62/PM06/NK1W 3000	IP54	3000	15	2000	1420	3	0,9	60
53251	LED-1L14B07KN62/PM06/NK1W 3000	IP54	3000	20	2590	1840	3	0,9	60
56714	LED-1L14C03KN62/PM06/NK1W 4000	IP54	4000	15	2110	1500	3	0,9	60
53751	LED-1L14B07KN62/PM06/NK1W 4000	IP54	4000	20	2700	1920	3	0,9	60
Emergency combined + sensor									
56215	LED-1L14C03KN62/PM06/NK1W HF 3000	IP54	3000	15	2000	1420	3	0,9	60
53253	LED-1L14B07KN62/PM06/NK1W HF 3000	IP54	3000	20	2590	1840	3	0,9	60
56715	LED-1L14C03KN62/PM06/NK1W HF 4000	IP54	4000	15	2110	1500	3	0,9	60
53753	LED-1L14B07KN62/PM06/NK1W HF 4000	IP54	4000	20	2700	1920	3	0,9	60