



TILIA 2

Dimensions:	400x400 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polycarbonate (PC)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56171	IN-32NU3/PC33	IP44		3x30	3xE27		2,2	24
56172	E-26NU3/PC33 32W	IP44		2x32	2xGX24q3		2,6	24
56173	E-27NU3/PC33	IP44		2x36	2xG10		2,6	24
Sensor								
56177	IN-32NU3/PC33 HF	IP44		3x30	3xE27		2,3	24
Emergency combined								
56180	NKC-232/16/PC33	IP44		2x32	2xGX24q3	1	2,9	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56363	LED-1L33C10NU3/PC33 3000	IP44	3000	28	3690	2470		2,2	60
53423	LED-1L33B07NU3/PC33 3000	IP44	3000	36	4850	3250		2,2	60
56863	LED-1L33C10NU3/PC33 4000	IP44	4000	28	3890	2610		2,2	60
53923	LED-1L33B07NU3/PC33 4000	IP44	4000	36	5070	3400		2,2	60
Sensor									
56364	LED-1L33C10NU3/PC33 HF 3000	IP44	3000	28	3690	2470		2,2	60
53429	LED-1L33B07NU3/PC33 HF 3000	IP44	3000	36	4850	3250		2,2	60
56864	LED-1L33C10NU3/PC33 HF 4000	IP44	4000	28	3890	2610		2,2	60
53929	LED-1L33B07NU3/PC33 HF 4000	IP44	4000	36	5070	3400		2,2	60
Dimmable									
56365	LED-1L33C10NU3/PC33 DALI 3000	IP44	3000	28	3690	2470		2,2	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
53427	LED-1L33B07NU3/PC33 DALI 3000	IP44	3000	36	4850	3250		2,2	60
56865	LED-1L33C10NU3/PC33 DALI 4000	IP44	4000	28	3890	2610		2,2	60
53927	LED-1L33B07NU3/PC33 DALI 4000	IP44	4000	36	5070	3400		2,2	60
Emergency combined									
56368	LED-1L33C10NU3/PC33/NK1W 3000	IP44	3000	28	3690	2470	3	2,2	60
53431	LED-1L33B07NU3/PC33/NK1W 3000	IP44	3000	36	4850	3250	3	2,2	60
56868	LED-1L33C10NU3/PC33/NK1W 4000	IP44	4000	28	3890	2610	3	2,2	60
53931	LED-1L33B07NU3/PC33/NK1W 4000	IP44	4000	36	5070	3400	3	2,2	60
Emergency combined + sensor									
56369	LED-1L33C10NU3/PC33/NK1W HF 3000	IP44	3000	28	3690	2470	3	2,2	60
56370	LED-1L33B07NU3/PC33/NK1W HF 3000	IP44	3000	36	4850	3250	3	2,2	60
56869	LED-1L33C10NU3/PC33/NK1W HF 4000	IP44	4000	28	3890	2610	3	2,2	60
56870	LED-1L33B07NU3/PC33/NK1W HF 4000	IP44	4000	36	5070	3400	3	2,2	60
Two-circuits									
53425	LED-1L33B07NU3/PC33 2/1 3000	IP44	3000	36	4850	3250		2,2	60
53925	LED-1L33B07NU3/PC33 2/1 4000	IP44	4000	36	5070	3400		2,2	60
Corridor									
56366	LED-1L33C10NU3/PC33 DALI HF CORR 3000	IP44	3000	28	3690	2470		2,2	60
56367	LED-1L33B07NU3/PC33 DALI HF CORR 3000	IP44	3000	36	4850	3250		2,2	60
56866	LED-1L33C10NU3/PC33 DALI HF CORR 4000	IP44	4000	28	3890	2610		2,2	60
56867	LED-1L33B07NU3/PC33 DALI HF CORR 4000	IP44	4000	36	5070	3400		2,2	60