

DESCRIPTION

- Luminaire with direct luminous flux distribution, frost opal polycarbonate diffuser and aluminium body e ral 9005 matt black finish.





IP40

MAIN FEATURES

Weight (Kg)	5.6
Glow-wire Resistance	850°C
Input	220-240V~/50-60Hz
Control	ON/OFF Power Supply

TECHNICAL FEATURES

Luminous Flux Maintenance	L90
MAX Power (W)	16
Maximum Value (cd/Klm)	385
% LOR	100
Total Flux (lm)	2020
System Power (W)	18
Flux/Power (lm/W)	126
Color Temperature	4000K
Color Rendering Index (CRI)	>80
LED Efficiency	179 lm/W @Tc=45°C
MacAdam Ellipse	3
LED Degradation/Mortality	F10



STANDARDS

DIRECTIVE 2011/65/EU of 8 June 2011 + COMMISSION DELEGATED DIRECTIVE (EU) 2015/863 of 31 March 2015 RoHS2
DIRECTIVE 2014/30/EU of 26 February 2014
EN 50581:2012 | EN 55015:2006+A1:2007+A2:2009 | EN 60335-1:2012 | EN 60598-1: 2014 | EN 60598-2-1: 1990 | EN 60598-2-13: 2006 | EN 60598-2-2: 2014 | EN 60598-2-22: 2014 | EN 60598-2-25: 2009 | EN 60598-2-4: 2017 | EN 61000-4-2:2009;EN 61000-4-3:2006 + A1:2008;EN 61000-4-4:2004;EN 61000-4-5:2006;EN 61000-4-6:2009 | EN 61547:2009
LOW VOLTAGE DIRECTIVE 2014/35/EU of 26 February 2014