



ELSA 5

Dimensions:	ø 500 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	bayonet
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
54950	IN-32B16/626	IP20		3x60	3xE27		5,9	24
54952	E-204B16/626	IP20		22+40	2xGX13		6,0	24
54954	E-28B16/626	IP20		2x42	2xGX24q4		5,9	24
54963	IN-32BT16/626	IP44		3x60	3xE27		5,9	24
54965	E-204BT16/626	IP44		22+40	2xGX13		6,0	24
54967	E-28BT16/626	IP44		2x42	2xGX24q4		5,9	24
Emergency combined								
54962	NKC-232/16/626	IP20		2x32	2xGX24q3	1	6,4	24
54975	NKC-232/16/T/626	IP44		2x32	2xGX24q3	1	6,4	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
59091	LED-1L16C07BT16/626 3000	IP44	3000	28	3690	2400		7,5	60
51330	LED-1L16B07BT16/626 3000	IP44	3000	36	4850	3150		8,3	60
59591	LED-1L16C07BT16/626 4000	IP44	4000	28	3890	2530		7,5	60
51830	LED-1L16B07BT16/626 4000	IP44	4000	36	5070	3300		8,3	60
Sensor									
59092	LED-1L16C07BT16/626 HF 3000	IP44	3000	28	3690	2400		7,5	60
51336	LED-1L16B07BT16/626 HF 3000	IP44	3000	36	4850	3150		8,4	60
59592	LED-1L16C07BT16/626 HF 4000	IP44	4000	28	3890	2530		7,5	60
51836	LED-1L16B07BT16/626 HF 4000	IP44	4000	36	5070	3300		8,4	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Dimmable									
59093	LED-1L16C07BT16/626 DALI 3000	IP44	3000	28	3690	2400		7,5	60
51334	LED-1L16B07BT16/626 DALI 3000	IP44	3000	36	4850	3150		8,4	60
59593	LED-1L16C07BT16/626 DALI 4000	IP44	4000	28	3890	2530		7,5	60
51834	LED-1L16B07BT16/626 DALI 4000	IP44	4000	36	5070	3300		8,4	60
Emergency combined									
59097	LED-1L16C07BT16/626/NK1W 3000	IP44	3000	28	3690	2400	3	7,5	60
51338	LED-1L16B07BT16/626/NK1W 3000	IP44	3000	36	4850	3150	3	8,4	60
59597	LED-1L16C07BT16/626/NK1W 4000	IP44	4000	28	3890	2530	3	7,5	60
51838	LED-1L16B07BT16/626/NK1W 4000	IP44	4000	36	5070	3300	3	8,4	60
Two-circuits									
51332	LED-1L16B07BT16/626 2/1 3000	IP44	3000	36	4850	3150		8,4	60
51832	LED-1L16B07BT16/626 2/1 4000	IP44	4000	36	5070	3300		8,4	60
Corridor									
59094	LED-1L16C07BT16/626 DALI HF CORR 3000	IP44	3000	28	3690	2400		7,5	60
59096	LED-1L16B07BT16/626 DALI HF CORR 3000	IP44	3000	36	4850	3150		8,4	60
59594	LED-1L16C07BT16/626 DALI HF CORR 4000	IP44	4000	28	3890	2530		7,5	60
59596	LED-1L16B07BT16/626 DALI HF CORR 4000	IP44	4000	36	5070	3300		8,4	60