



AURA 5

Dimensions:	ø 490 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet (IP43)
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
40095	IN-32K86/082	IP43		3x60	3xE27		3,7	24
40097	E-27K86/082	IP43		2x36	2xG10		3,8	24
42309	E-28K86/082	IP43		2x42	2xGX24q4		3,8	24
Sensor								
46105	IN-22K86/082 HF	IP43		2x60	2xE27		3,8	24
Emergency combined								
46283	NKC-232/16/082	IP43		2x32	2xGX24q3	1	4,7	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
59034	LED-1L16C07K86/082 3000	IP43	3000	28	3690	2550		4,7	60
51244	LED-1L16B07K86/082 3000	IP43	3000	36	4850	3350		5,5	60
59534	LED-1L16C07K86/082 4000	IP43	4000	28	3890	2680		4,7	60
51744	LED-1L16B07K86/082 4000	IP43	4000	36	5070	3500		5,5	60
Sensor									
59035	LED-1L16C07K86/082 HF 3000	IP43	3000	28	3690	2550		4,7	60
51249	LED-1L16B07K86/082 HF 3000	IP43	3000	36	4850	3350		5,5	60
59535	LED-1L16C07K86/082 HF 4000	IP43	4000	28	3890	2680		4,7	60
51749	LED-1L16B07K86/082 HF 4000	IP43	4000	36	5070	3500		5,5	60
Dimmable									
59036	LED-1L16C07K86/082 DALI 3000	IP43	3000	28	3690	2550		4,7	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
51247	LED-1L16B07K86/082 DALI 3000	IP43	3000	36	4850	3350		5,5	60
59536	LED-1L16C07K86/082 DALI 4000	IP43	4000	28	3890	2680		4,7	60
51747	LED-1L16B07K86/082 DALI 4000	IP43	4000	36	5070	3500		5,5	60
Emergency combined									
59039	LED-1L16C07K86/082/NK1W 3000	IP43	3000	28	3690	2550	3	4,7	60
51251	LED-1L16B07K86/082/NK1W 3000	IP43	3000	36	4850	3350	3	5,5	60
59539	LED-1L16C07K86/082/NK1W 3000	IP43	3000	28	3690	2680	3	4,7	60
51751	LED-1L16B07K86/082/NK1W 3000	IP43	3000	36	4850	3500	3	5,5	60
Two-circuits									
51245	LED-1L16B07K86/082 2/1 3000	IP43	3000	36	4850	3350		5,5	60
51745	LED-1L16B07K86/082 2/1 4000	IP43	4000	36	5070	3500		5,5	60
Corridor									
59037	LED-1L16C07K86/082 DALI HF CORR 3000	IP43	3000	28	3690	2550		4,7	60
59038	LED-1L16B07K86/082 DALI HF CORR 3000	IP43	3000	36	4850	3350		5,5	60
59537	LED-1L16C07K86/082 DALI HF CORR 4000	IP43	4000	28	3890	2680		4,7	60
59538	LED-1L16B07K86/082 DALI HF CORR 4000	IP43	4000	36	5070	3500		5,5	60