


# TITAN 5

<b>Dimensions:</b>	ø 900 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	opal polymethylmetacrylate (PMMA)
<b>Shade attach.:</b>	two-step clamp holders
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
56061	IN-62KN11/PM11	IP44		6x40	6xE27		7,9	24
56062	E-66KN11/PM11	IP44		6x24	G5		8,3	24
56063	E-67KN11/PM11	IP44		6x36	6x2G10		9,1	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
56266	LED-9L52B07KN11/PM11 3000	IP54	3000	104	15310	10720		9,9	60
48224	LED-9L52B10KN11/PM11 3000	IP54	3000	165	22180	15530		10,0	60
56766	LED-9L52B07KN11/PM11 4000	IP54	4000	104	16000	11200		9,9	60
48724	LED-9L52B10KN11/PM11 4000	IP54	4000	165	23170	16220		10,0	60
<b>Dimmable</b>									
56267	LED-9L52B07KN11/PM11 DALI 3000	IP54	3000	104	15310	10720		9,9	60
48227	LED-9L52B10KN11/PM11 DALI 3000	IP54	3000	165	22180	15530		10,1	60
56767	LED-9L52B07KN11/PM11 DALI 4000	IP54	4000	104	16000	11200		9,9	60
48727	LED-9L52B10KN11/PM11 DALI 4000	IP54	4000	165	23170	16220		10,1	60
<b>Two-circuits</b>									
56268	LED-9L52B07KN11/PM11 2/1 3000	IP54	3000	104	15310	10720		9,9	60
48225	LED-9L52B10KN11/PM11 2/1 3000	IP54	3000	165	22180	15530		10,0	60
56768	LED-9L52B07KN11/PM11 2/1 4000	IP54	4000	104	16000	11200		9,9	60
48725	LED-9L52B10KN11/PM11 2/1 4000	IP54	4000	165	23170	16220		10,0	60