





ADRIA P4

Dimensions:	ø 500 mm
Color:	white
Type:	ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	steel holder (ø150mm)
Pendant:	rod
Length of pendant:	a1 - 200mm, a2 - 400mm, a3 - 600mm, a4 - 800mm, a5 - 1000mm
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
42192	Z11/098/a1 B	IP40		150	E27		5,0	24
42193	Z11/098/a2 B	IP40		150	E27		5,1	24
42194	Z11/098/a3 B	IP40		150	E27		5,2	24
42195	Z11/098/a4 B	IP40		150	E27		5,3	24
42196	Z11/098/a5 B	IP40		150	E27		5,4	24
44210	E-26Z11/098/a1 B 32W	IP40		2x32	2xGX24q3		5,4	24
44211	E-26Z11/098/a2 B 32W	IP40		2x32	2xGX24q3		5,5	24
44212	E-26Z11/098/a3 B 32W	IP40		2x32	2xGX24q3		5,6	24
44213	E-26Z11/098/a4 B 32W	IP40		2x32	2xGX24q3		5,7	24
44214	E-26Z11/098/a5 B 32W	IP40		2x32	2xGX24q3		5,8	24
42355	E-46Z11/098/a1 B	IP40		4x26	4xG24q3		5,7	24
42356	E-46Z11/098/a2 B	IP40		4x26	4xG24q3		5,8	24
42357	E-46Z11/098/a3 B	IP40		4x26	4xG24q3		5,8	24
42358	E-46Z11/098/a4 B	IP40		4x26	4xG24q3		5,9	24
42359	E-46Z11/098/a5 B	IP40		4x26	4xG24q3		6,0	24
Dimmable								
45200	ES-46Z11/098/a1 B DALI	IP40		4x26	4xG24q3		5,5	24
45201	ES-46Z11/098/a2 B DALI	IP40		4x26	4xG24q3		5,6	24
45202	ES-46Z11/098/a3 B DALI	IP40		4x26	4xG24q3		5,7	24
45203	ES-46Z11/098/a4 B DALI	IP40		4x26	4xG24q3		5,8	24
45204	ES-46Z11/098/a5 B DALI	IP40		4x26	4xG24q3		5,9	24
Emergency combined								
45205	NKC-232Z11/16/098/a1 B	IP40		2x32	2xGX24q3	1	5,6	24
45206	NKC-232Z11/16/098/a2 B	IP40		2x32	2xGX24q3	1	5,7	24

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
45207	NKC-232Z11/16/098/a3 B	IP40		2x32	2xGX24q3	1	5,8	24
45208	NKC-232Z11/16/098/a4 B	IP40		2x32	2xGX24q3	1	5,9	24
45209	NKC-232Z11/16/098/a5 B	IP40		2x32	2xGX24q3	1	6,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
------	------	----	---------	-----------	-----------------------	-----------------------------	-------	--------	------------------

Classic

60135	LED-5L07C09Z11/098/a1 B 3000	IP40	3000	44	5880	5170		6,4	60
60136	LED-5L07C09Z11/098/a2 B 3000	IP40	3000	44	5880	5170		6,4	60
60137	LED-5L07C09Z11/098/a3 B 3000	IP40	3000	44	5880	5170		6,4	60
60138	LED-5L07C09Z11/098/a4 B 3000	IP40	3000	44	5880	5170		6,4	60
60139	LED-5L07C09Z11/098/a5 B 3000	IP40	3000	44	5880	5170		6,4	60
60635	LED-5L07C09Z11/098/a1 B 4000	IP40	4000	44	6200	5450		6,4	60
60636	LED-5L07C09Z11/098/a2 B 4000	IP40	4000	44	6200	5450		6,4	60
60637	LED-5L07C09Z11/098/a3 B 4000	IP40	4000	44	6200	5450		6,4	60
60638	LED-5L07C09Z11/098/a4 B 4000	IP40	4000	44	6200	5450		6,4	60
60639	LED-5L07C09Z11/098/a5 B 4000	IP40	4000	44	6200	5450		6,4	60

Dimmable

60140	LED-5L07C09Z11/098/a1 B DALI 3000	IP40	3000	44	5880	5170		6,4	60
60141	LED-5L07C09Z11/098/a2 B DALI 3000	IP40	3000	44	5880	5170		6,4	60
60142	LED-5L07C09Z11/098/a3 B DALI 3000	IP40	3000	44	5880	5170		6,4	60
60143	LED-5L07C09Z11/098/a4 B DALI 3000	IP40	3000	44	5880	5170		6,4	60
60144	LED-5L07C09Z11/098/a5 B DALI 3000	IP40	3000	44	5880	5170		6,4	60
60640	LED-5L07C09Z11/098/a1 B DALI 4000	IP40	4000	44	6200	5450		6,4	60
60641	LED-5L07C09Z11/098/a2 B DALI 4000	IP40	4000	44	6200	5450		6,4	60
60642	LED-5L07C09Z11/098/a3 B DALI 4000	IP40	4000	44	6200	5450		6,4	60
60643	LED-5L07C09Z11/098/a4 B DALI 4000	IP40	4000	44	6200	5450		6,4	60
60644	LED-5L07C09Z11/098/a5 B DALI 4000	IP40	4000	44	6200	5450		6,4	60

Emergency combined

60145	LED-5L07C09Z11/098/a1/NK1W B 3000	IP40	3000	44	5880	5170	3	6,4	60
60146	LED-5L07C09Z11/098/a2/NK1W B 3000	IP40	3000	44	5880	5170	3	6,4	60
60147	LED-5L07C09Z11/098/a3/NK1W B 3000	IP40	3000	44	5880	5170	3	6,4	60
60148	LED-5L07C09Z11/098/a4/NK1W B 3000	IP40	3000	44	5880	5170	3	6,4	60
60149	LED-5L07C09Z11/098/a5/NK1W B 3000	IP40	3000	44	5880	5170	3	6,4	60
60645	LED-5L07C09Z11/098/a1/NK1W B 4000	IP40	4000	44	6200	5450	3	6,4	60
60646	LED-5L07C09Z11/098/a2/NK1W B 4000	IP40	4000	44	6200	5450	3	6,4	60
60647	LED-5L07C09Z11/098/a3/NK1W B 4000	IP40	4000	44	6200	5450	3	6,4	60
60648	LED-5L07C09Z11/098/a4/NK1W B 4000	IP40	4000	44	6200	5450	3	6,4	60
60649	LED-5L07C09Z11/098/a5/NK1W B 4000	IP40	4000	44	6200	5450	3	6,4	60