


TILIA 1

Dimensions:	300x300 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polycarbonate (PC)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
56155	IN-22NU2/PC32	IP44		2x30	2xE27		1,3	24
56157	E-25NU2/PC32	IP44		2x18	2xG24q2		1,6	24
56158	E-26NU2/PC32	IP44		2x26	2xG24q3		1,6	24
Sensor								
56159	IN-22NU2/PC32 HF	IP44		2x30	2xE27		1,4	24
Emergency combined								
56162	NKC-218/13/PC32	IP44		2x18	2xG24q2	1	2,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56355	LED-1L32C07NU2/PC32 3000	IP44	3000	19	2460	1750		1,5	60
53406	LED-1L32B07NU2/PC32 3000	IP44	3000	25	3230	2290		1,5	60
56855	LED-1L32C07NU2/PC32 4000	IP44	4000	19	2590	1840		1,5	60
53906	LED-1L32B07NU2/PC32 4000	IP44	4000	25	3380	2400		1,5	60
Sensor									
56356	LED-1L32C07NU2/PC32 HF 3000	IP44	3000	19	2460	1750		1,5	60
53411	LED-1L32B07NU2/PC32 HF 3000	IP44	3000	25	3230	2290		1,5	60
56856	LED-1L32C07NU2/PC32 HF 4000	IP44	4000	19	2590	1840		1,5	60
53911	LED-1L32B07NU2/PC32 HF 4000	IP44	4000	25	3380	2400		1,5	60
Dimmable									
56357	LED-1L32C07NU2/PC32 DALI 3000	IP44	3000	19	2460	1750		1,5	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
53409	LED-1L32B07NU2/PC32 DALI 3000	IP44	3000	25	3230	2290		1,5	60
56857	LED-1L32C07NU2/PC32 DALI 4000	IP44	4000	19	2590	1840		1,5	60
53909	LED-1L32B07NU2/PC32 DALI 4000	IP44	4000	25	3380	2400		1,5	60
Emergency combined									
56360	LED-1L32C07NU2/PC32/NK1W 3000	IP44	3000	19	2460	1750	3	1,5	60
53413	LED-1L32B07NU2/PC32/NK1W 3000	IP44	3000	25	3230	2290	3	1,5	60
56860	LED-1L32C07NU2/PC32/NK1W 4000	IP44	4000	19	2590	1840	3	1,5	60
53913	LED-1L32B07NU2/PC32/NK1W 4000	IP44	4000	25	3380	2400	3	1,5	60
Emergency combined + sensor									
56361	LED-1L32C07NU2/PC32/NK1W HF 3000	IP44	3000	19	2460	1750	3	1,5	60
56362	LED-1L32B07NU2/PC32/NK1W HF 3000	IP44	3000	25	3230	2290	3	1,5	60
56861	LED-1L32C07NU2/PC32/NK1W HF 4000	IP44	4000	19	2590	1840	3	1,5	60
56862	LED-1L32B07NU2/PC32/NK1W HF 4000	IP44	4000	25	3380	2400	3	1,5	60
Two-circuits									
53407	LED-1L32B07NU2/PC32 2/1 3000	IP44	3000	25	3230	2290		1,5	60
53907	LED-1L32B07NU2/PC32 2/1 4000	IP44	4000	25	3380	2400		1,5	60
Corridor									
56358	LED-1L32C07NU2/PC32 DALI HF CORR 3000	IP44	3000	19	2460	1750		1,5	60
56359	LED-1L32B07NU2/PC32 DALI HF CORR 3000	IP44	3000	25	3230	2290		1,5	60
56858	LED-1L32C07NU2/PC32 DALI HF CORR 4000	IP44	4000	19	2590	1840		1,5	60
56859	LED-1L32B07NU2/PC32 DALI HF CORR 4000	IP44	4000	25	3380	2400		1,5	60