



# TILIA 2A

<b>Dimensions:</b>	360x360 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	opal polycarbonate (PC)
<b>Shade attach.:</b>	two-step clamp holders
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
------	------	----	--------	-----------	--------	-------	--------	------------------

### Classic

<b>NEW</b> 52575	IN-22NU5/PC35	IP44		2x30	2xE27		1,0	60
------------------	---------------	------	--	------	-------	--	-----	----

### Sensor

<b>NEW</b> 52576	IN-22NU5/PC35 HF	IP44		2x30	2xE27		1,0	24
------------------	------------------	------	--	------	-------	--	-----	----

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
------	------	----	---------	-----------	-----------------------	-----------------------------	-------	--------	------------------

### Classic











<b>NEW</b> 67260	LED-1L34B05NU5/PC35 3000	IP54	3000	19	2700	1770		1,0	60
<b>NEW</b> 67266	LED-1L34B07NU5/PC35 3000	IP54	3000	27	3650	2390		1,0	60
<b>NEW</b> 67760	LED-1L34B05NU5/PC35 4000	IP54	4000	19	2830	1850		1,0	60
<b>NEW</b> 67766	LED-1L34B07NU5/PC35 4000	IP54	4000	27	3810	2490		1,0	60

### Sensor

<b>NEW</b> 67261	LED-1L34B05NU5/PC35 HF 3000	IP54	3000	19	2700	1770		1,0	24
<b>NEW</b> 67267	LED-1L34B07NU5/PC35 HF 3000	IP54	3000	27	3650	2390		1,0	24
<b>NEW</b> 67761	LED-1L34B05NU5/PC35 HF 4000	IP54	4000	19	2830	1850		1,0	24
<b>NEW</b> 67767	LED-1L34B07NU5/PC35 HF 4000	IP54	4000	27	3810	2490		1,0	24

### Dimmable

<b>NEW</b> 67262	LED-1L34B05NU5/PC35 DALI 3000	IP54	3000	19	2700	1770		1,0	60
<b>NEW</b> 67268	LED-1L34B07NU5/PC35 DALI 3000	IP54	3000	27	3650	2390		1,0	60
<b>NEW</b> 67762	LED-1L34B05NU5/PC35 DALI 4000	IP54	4000	19	2830	1850		1,0	60
<b>NEW</b> 67768	LED-1L34B07NU5/PC35 DALI 4000	IP54	4000	27	3810	2490		1,0	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Emergency combined</b>									
 67264	LED-1L34B05NU5/PC35/NK1W 3000	IP54	3000	19	2700	1770	3	2,0	24
 67270	LED-1L34B07NU5/PC35/NK1W 3000	IP54	3000	27	3650	2390	3	2,0	24
 67764	LED-1L34B05NU5/PC35/NK1W 4000	IP54	4000	19	2830	1850	3	2,0	24
 67770	LED-1L34B07NU5/PC35/NK1W 4000	IP54	4000	27	3810	2490	3	2,0	24
<b>Emergency combined + sensor</b>									
 67265	LED-1L34B05NU5/PC35/NK1W HF 3000	IP54	3000	19	2700	1770	3	2,0	24
 67271	LED-1L34B07NU5/PC35/NK1W HF 3000	IP54	3000	27	3650	2390	3	2,0	24
 67765	LED-1L34B05NU5/PC35/NK1W HF 4000	IP54	4000	19	2830	1850	3	2,0	24
 67771	LED-1L34B07NU5/PC35/NK1W HF 4000	IP54	4000	27	3810	2490	3	2,0	24
<b>Corridor</b>									
 67263	LED-1L34B05NU5/PC35 DALI HF CORR 3000	IP54	3000	19	2700	1770		1,0	24
 67269	LED-1L34B07NU5/PC35 DALI HF CORR 3000	IP54	3000	27	3650	2390		1,0	24
 67763	LED-1L34B05NU5/PC35 DALI HF CORR 4000	IP54	4000	19	2830	1850		1,0	24
 67769	LED-1L34B07NU5/PC35 DALI HF CORR 4000	IP54	4000	27	3810	2490		1,0	24