


DELIA 1A - PC

Dimensions:	ø 220 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polycarbonate (PC)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
52112	IN-12KN32/PC21	IP44		60	E27		0,0	24
Sensor								
52113	IN-12KN32/PC21 HF	IP44		40	E27		0,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
56280	LED-1L12C03KN32/PC21 3000	IP54	3000	9	1080	800		0,0	60
56282	LED-1L12B07KN32/PC21 3000	IP54	3000	11	1290	950		0,0	60
56780	LED-1L12C03KN32/PC21 4000	IP54	4000	9	1140	840		0,0	60
56782	LED-1L12B07KN32/PC21 4000	IP54	4000	11	1350	1000		0,0	60
Emergency									
56784	LED-NZ1W/PC21 4000	IP54	4000	1	170/150	110		0,0	60
Sensor									
56281	LED-1L12C03KN32/PC21 HF 3000	IP54	3000	9	1080	800		0,0	60
56283	LED-1L12B07KN32/PC21 HF 3000	IP54	3000	11	1290	950		0,0	60
56781	LED-1L12C03KN32/PC21 HF 4000	IP54	4000	9	1140	840		0,0	60
56783	LED-1L12B07KN32/PC21 HF 4000	IP54	4000	11	1350	1000		0,0	60