


# ELSA 1

<b>Dimensions:</b>	ø 250 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	handmade three-layer glass TRIPLEX OPAL (matt finish)
<b>Shade attach.:</b>	bayonet
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
44700	IN-12B12/023	IP20		75	E27		1,4	24
44702	E-14B12/023	IP20		13	G24q1		1,6	24
44703	E-15B12/023	IP20		18	G24q2		1,6	24
44705	IN-12BT12/023	IP44		75	E27		1,5	24
44707	E-14BT12/023	IP44		13	G24q1		1,7	24
44708	E-15BT12/023	IP44		18	G24q2		1,7	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
59066	LED-1L12C03BT12/023 3000	IP44	3000	9	1080	760		1,7	60
51296	LED-1L12B07BT12/023 3000	IP44	3000	11	1290	900		1,7	60
59566	LED-1L12C03BT12/023 4000	IP44	4000	9	1140	800		1,7	60
51796	LED-1L12B07BT12/023 4000	IP44	4000	11	1350	950		1,7	60
<b>Emergency</b>									
49774	LED-NZ1W/023 4000	IP44	4000	1	150	110	3	2,3	60
<b>Sensor</b>									
59067	LED-1L12C03BT12/023 HF 3000	IP44	3000	9	1080	760		1,7	60
51298	LED-1L12B07BT12/023 HF 3000	IP44	3000	11	1290	900		1,7	60
59567	LED-1L12C03BT12/023 HF 4000	IP44	4000	9	1140	800		1,7	60
51798	LED-1L12B07BT12/023 HF 4000	IP44	4000	11	1350	950		1,7	60
<b>Dimmable</b>									
59068	LED-1L12C03BT12/023 DALI 3000	IP44	3000	9	1080	760		1,7	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
59069	LED-1L12B07BT12/023 DALI 3000	IP44	3000	11	1290	900		1,7	60
59568	LED-1L12C03BT12/023 DALI 4000	IP44	4000	9	1140	800		1,7	60
59569	LED-1L12B07BT12/023 DALI 4000	IP44	4000	11	1350	950		1,7	60