





ADRIA P3

Dimensions:	ø 400 mm
Color:	white
Type:	ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	steel holder (ø150mm)
Pendant:	rod
Length of pendant:	a1 - 200mm, a2 - 400mm, a3 - 600mm, a4 - 800mm, a5 - 1000mm
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
42162	Z11/096/a1 B	IP40		150	E27		3,7	24
42163	Z11/096/a2 B	IP40		150	E27		3,8	24
42164	Z11/096/a3 B	IP40		150	E27		3,9	24
42165	Z11/096/a4 B	IP40		150	E27		4,0	24
42166	Z11/096/a5 B	IP40		150	E27		4,1	24
42167	E-26Z11/096/a1 B	IP40		2x26	2xG24q3		4,0	24
42168	E-26Z11/096/a2 B	IP40		2x26	2xG24q3		4,1	24
42169	E-26Z11/096/a3 B	IP40		2x26	2xG24q3		4,2	24
42170	E-26Z11/096/a4 B	IP40		2x26	2xG24q3		4,2	24
42171	E-26Z11/096/a5 B	IP40		2x26	2xG24q3		4,3	24
45060	E-28Z11/096/a1 B	IP40		2x42	2xGX24q4		4,0	24
45061	E-28Z11/096/a2 B	IP40		2x42	2xGX24q4		4,1	24
45062	E-28Z11/096/a3 B	IP40		2x42	2xGX24q4		4,2	24
45063	E-28Z11/096/a4 B	IP40		2x42	2xGX24q4		4,2	24
45064	E-28Z11/096/a5 B	IP40		2x42	2xGX24q4		4,3	24
Dimmable								
45075	ES-26Z11/096/a1 B DALI	IP40		2x26	2xG24q3		4,0	24
45076	ES-26Z11/096/a2 B DALI	IP40		2x26	2xG24q3		4,1	24
45077	ES-26Z11/096/a3 B DALI	IP40		2x26	2xG24q3		4,2	24
45078	ES-26Z11/096/a4 B DALI	IP40		2x26	2xG24q3		4,2	24
45079	ES-26Z11/096/a5 B DALI	IP40		2x26	2xG24q3		4,3	24
Emergency combined								
45080	NKC-226Z11/13/096/a1 B	IP40		2x26	2xG24q3	1	4,1	24
45081	NKC-226Z11/13/096/a2 B	IP40		2x26	2xG24q3	1	4,2	24

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
45082	NKC-226Z11/13/096/a3 B	IP40		2x26	2xG24q3	1	4,3	24
45083	NKC-226Z11/13/096/a4 B	IP40		2x26	2xG24q3	1	4,4	24
45084	NKC-226Z11/13/096/a5 B	IP40		2x26	2xG24q3	1	4,5	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
------	------	----	---------	-----------	-----------------------	-----------------------------	-------	--------	------------------

Classic

60075	LED-5L06C06Z11/096/a1 B 3000	IP40	3000	29	3900	3430		5,0	60
60076	LED-5L06C06Z11/096/a2 B 3000	IP40	3000	29	3900	3430		5,0	60
60077	LED-5L06C06Z11/096/a3 B 3000	IP40	3000	29	3900	3430		5,0	60
60078	LED-5L06C06Z11/096/a4 B 3000	IP40	3000	29	3900	3430		5,0	60
60079	LED-5L06C06Z11/096/a5 B 3000	IP40	3000	29	3900	3430		5,0	60
60575	LED-5L06C06Z11/096/a1 B 4000	IP40	4000	29	4110	3620		5,0	60
60576	LED-5L06C06Z11/096/a2 B 4000	IP40	4000	29	4110	3620		5,0	60
60577	LED-5L06C06Z11/096/a3 B 4000	IP40	4000	29	4110	3620		5,0	60
60578	LED-5L06C06Z11/096/a4 B 4000	IP40	4000	29	4110	3620		5,0	60
60579	LED-5L06C06Z11/096/a5 B 4000	IP40	4000	29	4110	3620		5,0	60

Dimmable

60080	LED-5L06C06Z11/096/a1 B DALI 3000	IP40	3000	29	3900	3430		5,0	60
60081	LED-5L06C06Z11/096/a2 B DALI 3000	IP40	3000	29	3900	3430		5,0	60
60082	LED-5L06C06Z11/096/a3 B DALI 3000	IP40	3000	29	3900	3430		5,0	60
60083	LED-5L06C06Z11/096/a4 B DALI 3000	IP40	3000	29	3900	3430		5,0	60
60084	LED-5L06C06Z11/096/a5 B DALI 3000	IP40	3000	29	3900	3430		5,0	60
60580	LED-5L06C06Z11/096/a1 B DALI 4000	IP40	4000	29	4110	3620		5,0	60
60581	LED-5L06C06Z11/096/a2 B DALI 4000	IP40	4000	29	4110	3620		5,0	60
60582	LED-5L06C06Z11/096/a3 B DALI 4000	IP40	4000	29	4110	3620		5,0	60
60583	LED-5L06C06Z11/096/a4 B DALI 4000	IP40	4000	29	4110	3620		5,0	60
60584	LED-5L06C06Z11/096/a5 B DALI 4000	IP40	4000	29	4110	3620		5,0	60