


# DELIA 4

|                       |                                   |
|-----------------------|-----------------------------------|
| <b>Dimensions:</b>    | ø 650 mm                          |
| <b>Color:</b>         | white                             |
| <b>Type:</b>          | wall or ceiling mounted           |
| <b>Shade:</b>         | opal polymethylmetacrylate (PMMA) |
| <b>Shade attach.:</b> | two-step clamp holders            |
| <b>Fixture:</b>       | powder coated steel sheet         |
| <b>Equipment:</b>     | STANDARD, LED                     |



## Standard

| Code           | Type           | IP   | Source | Input [W] | Socket | T [h] | m [kg] | Warranty [month] |
|----------------|----------------|------|--------|-----------|--------|-------|--------|------------------|
| <b>Classic</b> |                |      |        |           |        |       |        |                  |
| 53505          | IN-42KN10/PM25 | IP44 |        | 4x30      | 4xE27  |       | 5,0    | 24               |
| 53507          | E-47KN10/PM25  | IP44 |        | 4x36      | 4x2G10 |       | 5,3    | 24               |

## LED

| Code                | Type                           | IP   | CCT [K] | Input [W] | Lum. flux of LED [lm] | Lum. flux of luminaire [lm] | T [h] | m [kg] | Warranty [month] |
|---------------------|--------------------------------|------|---------|-----------|-----------------------|-----------------------------|-------|--------|------------------|
| <b>Classic</b>      |                                |      |         |           |                       |                             |       |        |                  |
| 56340               | LED-6L51B07KN10/PM25 3000      | IP54 | 3000    | 68        | 10210                 | 6940                        |       | 5,8    | 60               |
| 48228               | LED-6L51B10KN10/PM25 3000      | IP54 | 3000    | 109       | 14790                 | 10060                       |       | 5,5    | 60               |
| 56840               | LED-6L51B07KN10/PM25 4000      | IP54 | 4000    | 68        | 10670                 | 7260                        |       | 5,8    | 60               |
| 48728               | LED-6L51B10KN10/PM25 4000      | IP54 | 4000    | 109       | 15450                 | 10510                       |       | 5,5    | 60               |
| <b>Dimmable</b>     |                                |      |         |           |                       |                             |       |        |                  |
| 56341               | LED-6L51B07KN10/PM25 DALI 3000 | IP54 | 3000    | 68        | 10210                 | 6940                        |       | 5,8    | 60               |
| 48231               | LED-6L51B10KN10/PM25 DALI 3000 | IP54 | 3000    | 109       | 14790                 | 10060                       |       | 5,6    | 60               |
| 56841               | LED-6L51B07KN10/PM25 DALI 4000 | IP54 | 4000    | 68        | 10670                 | 7260                        |       | 5,8    | 60               |
| 48731               | LED-6L51B10KN10/PM25 DALI 4000 | IP54 | 4000    | 109       | 15450                 | 10510                       |       | 5,6    | 60               |
| <b>Two-circuits</b> |                                |      |         |           |                       |                             |       |        |                  |
| 56342               | LED-6L51B07KN10/PM25 2/1 3000  | IP54 | 3000    | 68        | 10210                 | 6940                        |       | 5,8    | 60               |
| 48229               | LED-6L51B10KN10/PM25 2/1 3000  | IP54 | 3000    | 109       | 14790                 | 10060                       |       | 5,5    | 60               |
| 56842               | LED-6L51B07KN10/PM25 2/1 4000  | IP54 | 4000    | 68        | 10670                 | 7260                        |       | 5,8    | 60               |
| 48729               | LED-6L51B10KN10/PM25 2/1 4000  | IP54 | 4000    | 109       | 15450                 | 10510                       |       | 5,5    | 60               |