


ADRIA P5

Dimensions:	ø 600 mm
Color:	white
Type:	ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	steel holder (ø150mm)
Pendant:	rod
Length of pendant:	a1 - 200mm, a2 - 400mm, a3 - 600mm, a4 - 800mm, a5 - 1000mm
Fixture:	powder coated steel sheet
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
45705	Z11/3/099/a1 B	IP40		3x60	3xE27		5,0	24
45706	Z11/3/099/a2 B	IP40		3x60	3xE27		5,0	24
45707	Z11/3/099/a3 B	IP40		3x60	3xE27		5,0	24
45708	Z11/3/099/a4 B	IP40		3x60	3xE27		5,0	24
45709	Z11/3/099/a5 B	IP40		3x60	3xE27		5,0	24
45715	E-48Z11/099/a1 B	IP40		4x42	4xGX24q4		5,0	24
45716	E-48Z11/099/a2 B	IP40		4x42	4xGX24q4		5,0	24
45717	E-48Z11/099/a3 B	IP40		4x42	4xGX24q4		5,0	24
45718	E-48Z11/099/a4 B	IP40		4x42	4xGX24q4		5,0	24
45719	E-48Z11/099/a5 B	IP40		4x42	4xGX24q4		5,0	24
Dimmable								
45725	ES-48Z11/099/a1 B DALI	IP40		4x42	4xGX24q4		5,0	24
45726	ES-48Z11/099/a2 B DALI	IP40		4x42	4xGX24q4		5,0	24
45727	ES-48Z11/099/a3 B DALI	IP40		4x42	4xGX24q4		5,0	24
45728	ES-48Z11/099/a4 B DALI	IP40		4x42	4xGX24q4		5,0	24
45729	ES-48Z11/099/a5 B DALI	IP40		4x42	4xGX24q4		5,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
60195	LED-5L07C10Z11/099/a1 B 3000	IP40	3000	51	6780	5970		7,0	60
60196	LED-5L07C10Z11/099/a2 B 3000	IP40	3000	51	6780	5970		7,0	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
60197	LED-5L07C10Z11/099/a3 B 3000	IP40	3000	51	6780	5970		7,0	60
60198	LED-5L07C10Z11/099/a4 B 3000	IP40	3000	51	6780	5970		7,0	60
60199	LED-5L07C10Z11/099/a5 B 3000	IP40	3000	51	6780	5970		7,0	60
60695	LED-5L07C10Z11/099/a1 B 4000	IP40	4000	51	7150	6290		7,0	60
60696	LED-5L07C10Z11/099/a2 B 4000	IP40	4000	51	7150	6290		7,0	60
60697	LED-5L07C10Z11/099/a3 B 4000	IP40	4000	51	7150	6290		7,0	60
60698	LED-5L07C10Z11/099/a4 B 4000	IP40	4000	51	7150	6290		7,0	60
60699	LED-5L07C10Z11/099/a5 B 4000	IP40	4000	51	7150	6290		7,0	60
Dimmable									
60200	LED-5L07C10Z11/099/a1 B DALI 3000	IP40	3000	51	6780	5970		7,0	60
60201	LED-5L07C10Z11/099/a2 B DALI 3000	IP40	3000	51	6780	5970		7,0	60
60202	LED-5L07C10Z11/099/a3 B DALI 3000	IP40	3000	51	6780	5970		7,0	60
60203	LED-5L07C10Z11/099/a4 B DALI 3000	IP40	3000	51	6780	5970		7,0	60
60204	LED-5L07C10Z11/099/a5 B DALI 3000	IP40	3000	51	6780	5970		7,0	60
60700	LED-5L07C10Z11/099/a1 B DALI 4000	IP40	4000	51	7150	6290		7,0	60
60701	LED-5L07C10Z11/099/a2 B DALI 4000	IP40	4000	51	7150	6290		7,0	60
60702	LED-5L07C10Z11/099/a3 B DALI 4000	IP40	4000	51	7150	6290		7,0	60
60703	LED-5L07C10Z11/099/a4 B DALI 4000	IP40	4000	51	7150	6290		7,0	60
60704	LED-5L07C10Z11/099/a5 B DALI 4000	IP40	4000	51	7150	6290		7,0	60