


# ELSA 4

<b>Dimensions:</b>	ø 420 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	handmade three-layer glass TRIPLEX OPAL (matt finish)
<b>Shade attach.:</b>	bayonet
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
44886	IN-22B15/029	IP20		2x75	2xE27		3,6	24
44890	E-26B15/029	IP20		2x26	2xG24q3		3,6	24
44891	E-26B15/029 32W	IP20		2x32	2xGX24q3		3,6	24
44900	IN-22BT15/029	IP44		2x75	2xE27		3,6	24
44904	E-26BT15/029	IP44		2x26	2xG24q3		3,6	24
44905	E-26BT15/029 32W	IP44		2x32	2xGX24q3		3,6	24
<b>Sensor</b>								
44895	IN-22B15/029 HF	IP20		2x60	2xE27		3,7	24
44909	IN-22BT15/029 HF	IP44		2x60	2xE27		3,7	24
<b>Emergency combined</b>								
44898	NKC-226/13/029	IP20		2x26	2xG24q3	1	3,8	24
44912	NKC-226/13/T/029	IP44		2x26	2xG24q3	1	3,8	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
59083	LED-1L15C07BT15/029 3000	IP44	3000	21	2770	1860		3,7	60
51321	LED-1L15B07BT15/029 3000	IP44	3000	29	3880	2600		4,2	60
59583	LED-1L15C07BT15/029 4000	IP44	4000	21	2920	1960		3,7	60
51821	LED-1L15B07BT15/029 4000	IP44	4000	29	4050	2710		4,2	60
<b>Sensor</b>									
59084	LED-1L15C07BT15/029 HF 3000	IP44	3000	21	2770	1860		3,7	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
51326	LED-1L15B07BT15/029 HF 3000	IP44	3000	29	3880	2600		4,2	60
59584	LED-1L15C07BT15/029 HF 4000	IP44	4000	21	2920	1960		3,7	60
51826	LED-1L15B07BT15/029 HF 4000	IP44	4000	29	4050	2710		4,2	60
<b>Dimmable</b>									
59085	LED-1L15C07BT15/029 DALI 3000	IP44	3000	21	2770	1860		3,7	60
51324	LED-1L15B07BT15/029 DALI 3000	IP44	3000	29	3880	2600		4,2	60
59585	LED-1L15C07BT15/029 DALI 4000	IP44	4000	21	2920	1960		3,7	60
51824	LED-1L15B07BT15/029 DALI 4000	IP44	4000	29	4050	2710		4,2	60
<b>Emergency combined</b>									
59088	LED-1L15C07BT15/029/NK1W 3000	IP44	3000	21	2770	1860	3	3,7	60
51328	LED-1L15B07BT15/029/NK1W 3000	IP44	3000	29	3880	2600	3	4,2	60
59588	LED-1L15C07BT15/029/NK1W 4000	IP44	4000	21	2920	1960	3	3,7	60
51828	LED-1L15B07BT15/029/NK1W 4000	IP44	4000	29	4050	2710	3	4,2	60
<b>Emergency combined + sensor</b>									
59089	LED-1L15C07BT15/029/NK1W HF 3000	IP44	3000	21	2770	1860	3	3,7	60
59090	LED-1L15B07BT15/029/NK1W HF 3000	IP44	3000	29	3880	2600	3	4,2	60
59589	LED-1L15C07BT15/029/NK1W HF 4000	IP44	4000	21	2920	1960	3	3,7	60
59590	LED-1L15B07BT15/029/NK1W HF 4000	IP44	4000	29	4050	2710	3	4,2	60
<b>Two-circuits</b>									
51322	LED-1L15B07BT15/029 2/1 3000	IP44	3000	29	3880	2600		4,2	60
51822	LED-1L15B07BT15/029 2/1 4000	IP44	4000	29	4050	2710		4,2	60
<b>Corridor</b>									
59086	LED-1L15C07BT15/029 DALI HF CORR 3000	IP44	3000	21	2770	1860		3,7	60
59087	LED-1L15B07BT15/029 DALI HF CORR 3000	IP44	3000	29	3880	2600		4,2	60
59586	LED-1L15C07BT15/029 DALI HF CORR 4000	IP44	4000	21	2920	1960		3,7	60
59587	LED-1L15B07BT15/029 DALI HF CORR 4000	IP44	4000	29	4050	2710		4,2	60