



TRITON 1

Dimensions:	ø 280 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	opal polycarbonate (PC)
Shade attach.:	bayonet, a possibility of securing shade with a screw
Fixture:	polycarbonate molding
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
50080	IN-182 B	IP65 II		40	E27		0,0	24
50086	IN-182/2 B	IP65 II		2x25	2xE27		0,0	24
50082	E-183/26 B	IP65		26	G24q3		0,0	24
Sensor								
50081	IN-182 HF B	IP65		1x25	E27		0,0	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
57200	LED-1L14C03/IN-182 B 3000	IP65	3000	15	2000	1640		0,0	60
57203	LED-1L14B07/IN-182 B 3000	IP65	3000	20	2590	2120		0,0	60
57700	LED-1L14C03/IN-182 B 4000	IP65	4000	15	2110	1730		0,0	60
57703	LED-1L14B07/IN-182 B 4000	IP65	4000	20	2700	2210		0,0	60
Sensor									
57201	LED-1L14C03/IN-182 B HF 3000	IP65	3000	15	2000	1640		0,0	60
57204	LED-1L14B07/IN-182 B HF 3000	IP65	3000	20	2590	2120		0,0	60
57701	LED-1L14C03/IN-182 B HF 4000	IP65	4000	15	2110	1730		0,0	60
57704	LED-1L14B07/IN-182 B HF 4000	IP65	4000	20	2700	2210		0,0	60
Dimmable									
57202	LED-1L14C03/IN-182 B DALI 3000	IP65	3000	15	2000	1640		0,0	60
57205	LED-1L14B07/IN-182 B DALI 3000	IP65	3000	20	2590	2120		0,0	60
57702	LED-1L14C03/IN-182 B DALI 4000	IP65	4000	15	2110	1730		0,0	60
57705	LED-1L14B07/IN-182 B DALI 4000	IP65	4000	20	2700	2210		0,0	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Emergency combined									
57206	LED-1L14C03/IN-182/NK1W B 3000	IP65	3000	15	2000	1640	3	0,0	60
57207	LED-1L14B07/IN-182/NK1W B 3000	IP65	3000	20	2590	2120	3	0,0	60
57706	LED-1L14C03/IN-182/NK1W B 4000	IP65	4000	15	2110	1730	3	0,0	60
57707	LED-1L14B07/IN-182/NK1W B 4000	IP65	4000	20	2700	2210	3	0,0	60